# TOUGH2Viewer 2.0 Quick Tutorial R1 (2020)

Stefano Bonduà, Villiam Bortolotti DICAM

Università di Bologna

www.dicam.unibo.it

### Summary

| 1 | License a  | agreement                                    | 3  |
|---|------------|--|----|
| 2 | Introduct  | tion   | 3  |
| 3 | System F   | Requirements                                 | 4  |
|   | 3.1 Wine   | dows Java3D installation troubleshot         | 4  |
| 4 | Installati | on, execution and uninstallation instruction | 6  |
|   | 4.1 TOU    | JGH2Viewer installation                      | 6  |
|   | 4.2 TOU    | JGH2Viewer execution                         | 8  |
|   | 4.2.1      | Linux  | 8  |
|   | 4.2.2      | Windows                                      | 8  |
|   | 4.3 TOU    | JGH2Viewer uninstallation                    | 8  |
| 5 | TOUGH      | 2Viewer overview                             | 9  |
|   | 5.1 File   | menu   | 9  |
|   | 5.2 View   | v menu                                       | 9  |
|   | 5.3 Anal   | lysis  | 11 |
|   | 5.4 Tool   | s  | 13 |
| 6 | Tutorial   | Examples                                     | 14 |
|   | 6.1 Strue  | ctured grid model 2D                         | 14 |
|   | 6.1.1      | Load Files                                   | 14 |
|   | 6.1.2      | 3D Block Model view                          | 15 |
|   | 6.1.3      | 2D Contour Plot visualization                | 16 |
|   | 6.1.4      | 2D Flow Vector visualization                 | 17 |
|   | 6.1.5      | Statistics                                   | 18 |
|   | 6.2 Strue  | ctured 3D Grid model                         | 20 |
|   | 6.2.1      | Load Files                                   | 20 |
|   | 6.2.2      | Export Structured Data to Paraview           | 20 |
|   | 6.2.3      | 3D block model view                          | 21 |
|   | 6.2.4      | 3D Flow Vector visualization                 | 27 |
|   | 6.2.5      | 3D Iso Surface                               | 28 |
|   | 6.2.6      | 2D Contour Plot visualization                | 30 |
|   | 6.3 Unst   | ructured 3D grid model                       | 31 |
|   | 6.3.1      | Load Files                                   | 32 |
|   | 6.3.2      | 3D Block model view                          | 36 |
|   | 6.3.3      | 3D Flow Vector visualization                 | 41 |
|   | 6.3.4      | 3D Iso Surface                               | 42 |
|   | 6.3.5      | 2D Contour map                               | 43 |
|   | 6.3.6      | Statistics                                   | 44 |
|   | 6.4 Vore   | onoi 3D grid model                           | 45 |
|   | 6.4.1      | Load Files                                   | 45 |
|   | 6.4.2      | 3D Block model view                          | 46 |
|   | 6.4.3      | Prepare GENER file                           | 47 |
|   | 6.4.4      | Export data to Paraview                      | 51 |
|   | 6.5 The    | Amiata structured 3D grid case               | 52 |
| _ | 6.6 The    | structured grid case                         | 60 |
| 1 | Keterenc   | es   | /1 |
| 8 | List of fi | gures  | 12 |

# 1 License agreement

All computer programs (hereinafter collectively referred to as the 'Software') are downloadable from the webpage https://github.com/stebond/TOUGH2ViewerX and can be used only under the **Apache** License, Version 2.0 (<u>https://opensource.org/licenses/Apache-2.0</u>).

# 2 Introduction

TOUGH2Viewer is a Java program capable of displaying structured and unstructured (Voronoi complying) grids, and structured grids compliant with the TOUGH2 family of codes (Pruess et al. 1999).

In particular, TOUGH2Viewer allows the navigation through a 3D grid compatible with the TOUGH2 data file format and visualize:

- the thermodynamic variables and the material (namely, petrophysical properties) of each block;
- maps of isovalues (2D) of all thermodynamic variables;
- isosurfaces (3D) of all thermodynamic variables;
- flows of mass and heat between blocks;
- spatial profiles of thermodynamic variables along Cartesian direction;
- time plot of thermodynamic variables of a selected block.

All commands to manage a 3D visualization (zooming, pan, rotations) are CAD complying.

- In the following chapters, four tutorial examples will be presented:
  - 1. structured 2D grid generated with MESHMAKER.
  - 2. structured 3D grid generated with MESHMAKER.
  - 3. unstructured 3D (2.5D) grid generated with AMESH ().
  - 4. Fully unstructured 3D grid generated using VORO2MESH (Bonduà et. al, 2017)

All the example cases reported in this tutorial are simulation results obtained using the module EWASG (Battistelli et al., 1997) as implemented in iTOUGH2 (Pruess, 1999).

Related publications can be found in Bonduà et al. (2012, 2017), Berry et al. (2014).

# **3** System Requirements

The minimum system requirements to use TOUGH2Viewer are:

1GB of RAM;

100 MB of free disk space;

Graphic card equipped with 512 MB RAM;

Supported OS: Linux Ubuntu 8.04 or later, Windows XP, Vista, 7, 8 10.

TOUGH2Viewer requires Java<sup>™</sup> Runtime Environment (JRE) version 1.6.14 (or later) and the Java extension to display three dimensional graphics (Java3D) version 1.5.1 (or later) to be already installed on the system. To download installers and instruction manuals, please visit the official Oracle Web Site.

### 3.1 Windows Java3D installation troubleshot

Sometimes, the Java3D installation package cannot install properly the Java3D runtime libraries. Also, when the JRE is updated to a new version, the Java3D package will stop to work. It is possible to fix this issue by following the below procedure.

Run the Windows File Manager and locate the java folder. Usually, in the English version, it will be in the "C:\Program Files\Java" folder as showed Figure 1.

|  |                          |                   |             | 1 ×  |
|--|--------------------------|-------------------|-------------|------|
| Computer  Local Disk (C:)  | ▶ Program Files ▶ Java ▶ | ✓ 4 Search Java   |             | ٩    |
| Organize 🔻 Include in library 🔻 Share                                  | with  Vew folder         |                   |             | 0    |
| ☆ Favorites  | A Name                   | Date modified     | Туре        | Size |
| 📃 Desktop  | Java3D                   | 10/8/2012 3:33 PM | File folder |      |
| 👪 Downloads  | 📄 🥼 jre7                 | 10/8/2012 2:47 PM | File folder |      |
| Secent Places<br>Character<br>Documents<br>Music<br>Pictures<br>Videos | E                        |                   |             |      |
| -  | III                      |                   |             | F.   |
| 2 items  |                          |                   |             |      |

Figure 1 – Java folder.

Note: if you install the JRE 32 bit version, you will find the Java folder located at "C:\Program Files (x86)\Java". Therefore, in the following instructions you should use this path.

Copy the file "j3dcore-ogl.dll" from the folder "C:\Program Files\Java\Java3D1.5.2\bin\" (Figure 2) and paste it in the folder "C:\Program Files\Java\jre7\bin".

|   |  |                    |                    | ×    |
|---|--|--------------------|--------------------|------|
| 🕞 🗢 🕌 « Local Disk (C:) 🕨 Program File                        | s → Java → Java3D → 1.5.2 → bin -                        | ← Search bin       |                    | ٩    |
| Organize 🔻 🔳 Open with New folde                              | 1  |                    | H • 🔳              | 0    |
| 📃 Recent Places   | ^ Name   | Date modified      | Туре               | Size |
| 🚍 Liberrier   | 🚳 j3dcore-ogl.dll  | 6/30/2008 10:06 AM | Application extens |      |
| Documents  Music  Pictures  Videos  Computer                  | F  |                    |                    |      |
| 💒 Local Disk (C:)   |  |                    |                    |      |
| 🖵 VirtualPub2 (\\vboxsrv) (E:)                                |  |                    |                    |      |
|   | T (  |                    |                    | •    |
| j3dcore-ogl.dll Date modified:<br>Application extension Size: | 6/30/2008 10:06 AM Date created: 6/30/2008 10:<br>224 KB | 06 AM              |                    |      |

Figure 2 – j3dcore-ogl.dll location.

Copy the files j3dcore.jar, j3dutil.jar and vecmath.jar from the folder

"C:\Program Files\Java\Java3D\1.5.2\lib\ext" (Fig. 3), and paste them in the folder

"C:\Program Files\Java\jre7\lib\ext"

| ~ _  |                    |  |                    |                     | ×    |
|--|--------------------|--|--------------------|---------------------|------|
| 😋 🔵 🗢 🕌 « Program Files 🕨 Java 🕨 Ja          | iva3D ♦            | 1.5.2 • lib • ext                            | ✓ Search ext       |                     | م    |
| Organize 🔻 🏼 🔬 Open 🛛 New folder             |                    |  |                    | ····                | 0    |
| 📃 Recent Places                              | *                  | Name   | Date modified      | Туре                | Size |
| Contraction (Contraction)                    |                    | j3dcore                                      | 6/30/2008 10:06 AM | Executable Jar File |      |
| C Libraries                                  |                    | j3dutils                                     | 6/30/2008 10:06 AM | Executable Jar File |      |
| Documents                                    |                    | 🖉 vecmath                                    | 6/30/2008 10:06 AM | Executable Jar File |      |
| <ul> <li>Pictures</li> <li>Videos</li> </ul> | Ш                  |  |                    |                     |      |
| Computer                                     |                    |  |                    |                     |      |
| Local Disk (C:)                              |                    |  |                    |                     |      |
| VirtualPub2 (\\vboxsrv) (E:)                 | -                  | < [  | 11                 |                     | +    |
| 3 items selected Date modified:<br>Size:     | 6/30/20<br>4.75 MB | 008 10:06 AM Date created: 6/30/2008 10<br>B | :06 AM             |                     |      |

Fig. 3 – j3dcore.jar, j3dutil.jar and vecmath.jar folder.

If you have more than one java installation folder, e.g. jdk1.6.x.y etc., repeat steps from "a" to "d" for each folder.

# 4 Installation, execution and uninstallation instruction

## 4.1 TOUGH2Viewer installation

To install TOUGH2Viewer, user simply has to copy into a folder and unzip the compressed file (TOUGH2Viewer\_v.X.zip where X indicates the version) containing the whole software programs and examples. The unpacked package of files consists of two subdirectories, **dist** (standing for distribution) and **ExampleData**. In the examples described in this manual, the supposed folder will be "D:\T2Viewer\". So, at the end of the installation one should have a directory structure like the following:

#### D:\T2VIEWER

\---dist go.bat go1024.bat go1540.bat go2048.bat go3072.bat go4096.bat go6144.bat image.png iTough2Viewer.ini License.txt LogFile.txt path.ini README.TXT shape.ini splash.jpg tough2viewer.ini Tough2Viewer.jar voro\_pp.ini \---lib AbsoluteLayout.jar commons-math3-3.6.1.jar geoapi-2.3-M1.jar geoapi-pending-2.3-M1.jar gnujaxp.jar gt-api-2.7-M4.jar gt-coverage-2.7-M4.jar gt-data-2.7-M4.jar gt-geometry-2.7-M4.jar gt-its-wrapper-2.7-M4.jar gt-main-2.7-M4.jar gt-metadata-2.7-M4.jar gt-referencing-2.7-M4.jar gt-referencing3D-2.7-M4.jar gt-render-2.7-M4.jar gt-shapefile-2.7-M4.jar gt-shapefile-renderer-2.7-M4.jar gt-swing-2.7-M4.jar iText-2.1.5.jar j3dcore.jar j3dutils.jar jcommon-1.0.16.jar jfreechart-1.0.13-experimental.jar jfreechart-1.0.13-swt.jar jfreechart-1.0.13.jar jsr-275-1.0-beta-2.jar jts-1.11.jar junit.jar miglayout-3.7-swing.jar netcdfAll.jar

servlet.jar sgt-tutorial.jar swtgraphics2d.jar vecmath.jar visad.jar vtk.jar ExampleData| +---01\_Structured\_2D 2D.out MESH +---02\_Structured\_3D 3D\_F-im-w.out MESH.dat +---03\_Unstructured\_3D | 3d\_unstruct\_03.out L in.dat segmt.dat Т ∖---Maps +---base\_ss base\_ss.dbf base\_ss.prj base\_ss.qix base\_ss.shp base\_ss.shx base\_ss.xls \---Raster srtm\_dem +---04\_Voronoi\_3D MESH tough2viewer.dat voronoi3D.out +---05\_Amiata3D 01dem.dat 01dem.dat.ply 02fractured.dat 02fractured.dat.ply 03caprock\_shal.dat 03caprock\_shal.dat.ply 04shallow\_res.dat 04shallow\_res.dat.ply 05caprock\_deep.dat 05caprock\_deep.dat.ply 06bottom-5000.dat 06bottom-5000.dat.ply MESH tough2viewer.dat \---06\_Structured2D +---model MESH tough2viewer.dat INCON.dat ---Surfaces 00top.dat 00top.dat.ply 01top.dat 01top.dat.ply 02top.dat 02top.dat.ply 03top.dat 03top.dat.ply

### 4.2 TOUGH2Viewer execution

### 4.2.1 Linux

- 1. Navigate to the installation folder (/T2Viewer/dist/);
- 2. open a terminal window in "dist" folder
- 3. run the shell script, typing:

./**go.bat** [₊]

or typing:

*java -Xmx512M -jar Tough2Viewer.jar* [→]

Note that to reserve more RAM for TOUGH2Viewer execution, it is possible to use the others batch files allocating more MB (go1024.bat, go1540.bat, go2048.bat etc..)

### 4.2.2 Windows

1. Navigate to the installation folder (/T2Viewer/dist/);

2. double click on file "go.bat" or open a DOS prompt and type:

*java -Xmx512M -jar Tough2Viewer.jar* [↓]

Note that to reserve more RAM for TOUGH2Viewer execution, it is possible to use the others batch files allocating more MB (go1024.bat, go1540.bat, go2048.bat etc..)

## 4.3 TOUGH2Viewer uninstallation

To remove TOUGH2Viewer, just delete the installation folder containing all the files. To obtain information about how to remove JRE and Java3D, please consult the JRE and Java3D manuals or visit the Oracle official web site.

# **5** TOUGH2Viewer overview

TOUGH2viewer is a dialog based GUI for visualization and editing of TOUGH grids and simulation results. Details on the use of the menu items are reported in the chapter 6.

The main menu of TOUGH2Viewer contains the following items (Fig. 4 (a)):

- File: read grid and simulation results files;
- View: grid visualization;
- Analysis: results visualizations;
- Tools: visualization options and editing tools;
- ?: information about TOUGH2Viewer version.

| 🛓 TOUGH2Viewer 2.0         | _ | × | 🛓 TOUGH2Viewer 2.0 - 🗆 🗙   |
|----------------------------|---|---|----------------------------|
| File View Analysis Tools ? |   |   | File View Analysis Tools ? |
| File Information           |   |   | Open structured grid       |
| Grid type=                 |   |   | Open unstructured grid     |
| FileName =                 |   |   | Open unstructured V++ grid |
| FilePath=                  |   |   | Import Surface File        |
| n blocks=                  |   |   | Import wells               |
| Nodes coordinates:         |   |   | Mesh Generator             |
| xmin= xmax=                |   |   | Exit                       |
| ymin= ymax=                |   |   | ymin= ymax=                |
| zmin= zmax=                |   |   | zmin= zmax=                |
| Number of time steps=      |   |   | Number of time steps=      |
|                            |   |   |                            |
| University of Bologna      |   |   | (a) University of Bologna  |

Fig. 4 – (a) TOUGH2Viewer main dialog (b) File menu items.

### 5.1 File menu

The File menu Fig. 4 (b) allows the reading of several TOUGH grid files in different formats. File menu items are:

- Open structured grid: imports grid generated by MESHMAKER;
- Open unstructured grid: imports grid generated by AMESH;
- Open unstructured V++ grid: imports grid generated by VORO2MESH;
- Import Surface files: Import surface files (grid type or PLY file format);
- Import wells and Mesh Generator are still under development.

### 5.2 View menu

The **View** menu Fig. 5 allow grid and simulation results visualization. **View** menu items are:

- **3D Block model**: 3D grid visualization;
- **3D Flow vector**: 3d flow visualization;
- **3D Iso Surface**: Iso Surface generation;
- 2D Contour plots: contour plot of cross section of the model

• 2D Flow vector: flow visualization for 2D grids.



Fig. 5 – TOUGH2Viewer View menu.

All the visualization windows have a similar structure. In figure 5a it is shown that regarding the 3D block model visualization.



Fig. 5a - TOUGH2Viewer View menu.

These windows are characterized by three fundamental windows' controls:

- two combo-box to select the variable to be shown ("Variable" drop-down control) and the action to be performed on the grid model ("Action" drop-down control);

- a slider control to move among the range of simulated time steps.

The "Variable" drop-down control allows the user to select among the list of mutually exclusive variables computed in the loaded simulation file, as for example:

- Pressure P;
- Temperature T;

••••

The "Action" drop-down control allows the user to select among the list of mutually exclusive action that can be performed on the grid model showed. This list includes:

- ShiftXY, ShiftXZ, ShiftYZ to split the model by block clicking;
- **ResetPositions** to restore the model after the ShiftXY, ShiftXZ, ShiftYZ action;
- Get 2D Plot to obtain a vertical, horizontal or time dependent profiles of the selected block;
- TopView, LeftView, FrontView, RightView, BackView, BottomView, ParallelView, PerspectiveView, to change point of view and type of rendering;
- **setVOI** to definie a Volume of Interest;
- **SnapShot**: to export a image of the current view,
- **FindBlocks** to select a block by name;
- **ExpandZ**: to obtain a layerd view of the block;
- **QuickInfo**: to obtain information about the select mouse;
- **RealTimeInfo**: similar to QuickInfo, but with rollover anabled
- **SurfaceControl**: to modify surface appearance;
- **Directional profile**: similar to get2plot by in any horizontal direction (not just along x, y or z);
- **AutoSnapShot**: serialized image saving of the current view, iterating per varibles and/or time steps;
- **SelectNeighbord**: to activate the automatic selection of a selected blocks. By using this function is possible to export the selected blocks as a new MESH file;
- **MultipleSelection**: to select a set of blocks;
- **ModifySelection**: to change material and volume properties of the selected blocks;
- AdvancedBlocksSelection: a set of commands to allow block selection automation.

All the visualization windows (but also dialog windows) can be closed to return to the calling windows by clicking on the window icon  $\bowtie$  or the **Close** button.

## 5.3 Analysis

The Analysis menu allows plotting variables and computing statistic of the simulation results, and contains the following items:

- **Statistics**: global statistics of simulation results;
- **Heat and Mass Balance**: global behaviour of the variable plotted by the BALLA function of TOUGH as read from the simulation results;
- **Plot variables**: plotting of variables with one or two range axis.

| 🛓 tou   | GH2Vie                                |   | ×       |   |  |  |  |
|---|---------------------------------------|---|---------|---|--|--|--|
| File View   | Analysis                              | Tools ?   |         | - |  |  |  |
| File Infor<br>Grid typ<br>FileNam<br>FilePath<br>n blocks<br>Nodes o<br>xmin=<br>ymin=<br>zmin=<br>Number | Sta<br>He<br>Plc<br>s=<br>coordinates | tistics<br>at and Mass<br>of variables<br>s:<br>xmax=<br>ymax=<br>zmax=<br>eps= | Balance |   |  |  |  |
| University of Bologna   |                                       |   |         |   |  |  |  |

Fig. 6 – TOUGH2Viewer Analysis menu.

### 5.4 Tools

The Tool menu contains the following items (Fig. 7):

- **Options**: visualization settings and visualization options;
- **Color scale**: allows the preview and file export of the colour scale;
- **Test Java3D**: tests the correct Java3D installation;
- Create INCON: allows the generation of the INCON file as specified by the user.



Fig. 7 – TOUGH2Viewer Tools menu.

# 6 Tutorial Examples

These tutorials are designed to introduce to the TOUGH2Viewer basic features and should take less than one hour to be completed at all. Once finished, the user will have the skills to explore a 3D simulated model, plot variables and add to the 3D model frame own maps.

The following examples are supposed to be run under Windows operating system.

## 6.1 Structured grid model 2D

This example is related to the visualization of a 2D grid of 1800 blocks (50 along x, 1 along y and 36 files this tutorial load folder: along z). The for can be from the "D:\T2Viewer\ExampleData\01 Structured 2D". The disc letter D can change accordingly with the user installation.

In particular, two files are necessary:

- MESH ->the classical MESH file of TOUGH
- 2D.out->simulation results, this specific simulation was computed with the EOS EWASG.

Once TOUGH2Viewer is started, then the main window of TOUGH2Viewer will be displayed, as shown in Fig. 8.

| STOUGH2Viewer        |       |  |
|----------------------|-------|--|
| File View Analysis   | Tool  |  |
| File Information     |       |  |
| Grid type=           |       |  |
| FileName=            |       |  |
| FilePath=            |       |  |
| n blocks=            |       |  |
| Nodes coordinates:   |       |  |
| ×min=                | xmax= |  |
| ymin=                | ymax= |  |
| zmin=                | zmax= |  |
| Number of time step  |       |  |
|                      |       |  |
| University of Bologn | а     |  |

Fig. 8 - The TOUGH2Viewer empty main window.

### 6.1.1 Load Files

From the main menu, select the **File->Open structured grid** menu item to open the "Open structured grid" dialog window (Fig. 9).

| Open structured grid |                  |                        | × |
|----------------------|------------------|------------------------|---|
|                      |                  |                        |   |
| FileNameMesh         | Mesh File        |                        |   |
| FileNameOut          | Simulated File   |                        |   |
|                      | CreateEmptyModel | ExportTOUGH2Viewer.dat |   |
|                      | INCON            |                        |   |
| 0%                   |                  | Close                  |   |

Fig. 9 - The "Open structured grid" dialog window.

Click the **Mesh File** button to display the "Open mesh" dialog window. Browse, select and load the "MESH.dat" file (\T2Viewer\ExampleData\01\_Structured\_2D\MESH.dat).

This operation takes few seconds.

When loading is finished, the text box on the left side of the **Mesh File** button will contain the full path of the mesh file.

Click the **Simulated File** button to display the "Open Simulation" dialog window. Locate the TOUGH2 simulation output file "2d.out" and select it by clicking on it.

Then, click the Open button to start loading the file. The dialog progress bar will show the loading process and when it is arrived to 100 %, return to the main window clicking on the **Close** button.

Now in the main window will be shown some geometric information about the loaded model (see Fig. 10).

| 4                       | TOUGH2           | Viewer       |       |   |  |  |  |  |
|-------------------------|------------------|--------------|-------|---|--|--|--|--|
| File View Analysis Tool |                  |              |       |   |  |  |  |  |
|                         | File Information |              |       |   |  |  |  |  |
|                         | Grid type        | -            |       | 2D - xz - Structured grid                 |  |  |  |  |
|                         | FileName:        | =            |       | 2D.out                                    |  |  |  |  |
|                         | FilePath=        |              |       | D:\T2Viewer\ExampleData\01_Structured_2D\ |  |  |  |  |
|                         | n blocks=        | :            | 1800  |   |  |  |  |  |
|                         | Nodes co         | ordinates:   |       |   |  |  |  |  |
|                         | ×min=            | 50.0         | xmax= | 4950.0                                    |  |  |  |  |
|                         | ymin=            | 250.0        | ymax= | 250.0                                     |  |  |  |  |
|                         | zmin=            | -2950.0      | zmax= | 500.0                                     |  |  |  |  |
|                         | Number o         | f time steps | = 2   |   |  |  |  |  |
|                         |                  |              |       |   |  |  |  |  |
|                         |                  | 6 D - 1      |       |   |  |  |  |  |
|                         | University c     | of Bologna   |       |   |  |  |  |  |

Fig. 10 - Main window with geometric information of the loaded grid.

#### 6.1.2 3D Block Model view

From the main menu, click the **View->3D Block Model** menu item, to display the "3D Block Model" dialog window and to have the default 3D Model Frame view of the grid (in this specific case only with one block in the y coordinate), as shown in Fig. 11. The default variable showed in the dialog window is the first variable reported in the simulation output file (P for pressure in Fig. 4). Default action is **ShiftXY** (split the model using block clicking).



Fig. 11 - 3D Default representation of the Model, Top View.

From **Action** combo box, select "FrontView" to change view and then the plot frame is updated as shown in Fig. 5.



Fig. 12 - 3D representation of the model, FrontView.

Close the 3D Block model dialog by clicking the window icon icon or the **Close** button. For more detail on commands available for the 3D visualization management, see the example in chapter 6.2 and 6.3.

### 6.1.3 2D Contour Plot visualization

This functionality enables one to automatically compute and plot the contour lines of the primary variables.

In the main menu, click the **View->2D Contour plot** menu item and the default "2D Contour plot" dialog window displays. From the "Variable" combo box select a variable, for example **P** (pressure), then click the **Plot** button (Fig. 13).



Fig. 13 - Pressure contour map.

If *plot's* parameters, located on the left side of the dialog, are modified, then click the **Plot** button to update the plotting. As another example, in the right part of the window of Fig. 14 it is shown the contour plot of the temperature variable.



Fig. 14 - Temperature contour map

Close the 2D Contour plot dialog by clicking the window icon  $\bowtie$  or the **Close** button.

### 6.1.4 2D Flow Vector visualization

This functionality gives a 2D vector representation of the flow of heat or mass among blocks. In the main menu of TOUGH2Viewer, click the **View->2D Flow Vector** menu item to display the 2D Flow plot dialog window (see Fig. 8). The default plot shows the first variable that is present in the simulation output file, and the first-time step (FHEAT in the figure).



Fig. 15 - Vector map of the heat flow.

From the Variable combo box, select the VEL(LIQ.) item. Move the time slider to the last time step. Check the Normalize vectors check box and type 100 into Vector length text box. The 2D Flow vector dialog window now is as shown in Fig. 16.



Fig. 16 - Vector map of the variable VEL(LIQ.).

Close the 2D Flow vector dialog by clicking the window icon 🔀 or the Close button.

### 6.1.5 Statistics

In the "Statistics" dialog window is shown a table with the maximum and the minimum value for all the thermodynamic variables used in the simulation, and there is the possibility to plot a variable vs simulated time steps.

From the menu bar, click the **Analysis->Statistics** menu item. The Statistics dialog window is displayed (Fig. 17).



Fig. 17 - Min and Max value for simulation data. The default plot is first variable vs time.

To change the time steps, use the "Time" combo box. To change the plotted variable, use the "Variable" combo box.

Close the Statistic dialog by clicking the window icon  $\bowtie$  or the **Close** button.

Exit from TOUGH2Viewer by clicking the window icon or by the main menu item File->Exit.

## 6.2 Structured 3D Grid model

This example manages a 3D structured grid representing a spatial domain of  $5000x5000x3600 \text{ m}^3$  discretized in  $10 \times 10 \times 36$  blocks.

The files used in this example are

- MESH.dat -> the classical MESH file of TOUGH
- 3D\_F-im-w.out -> simulation results of a numerical model computed using EWASG.

both recorded in the folder "T2ViewerExampleData02\_Structured\_3D".

The simulation results contain two time steps.

Start TOUGH2Viewer (under Windows OS) by double clicking the **go.bat** batch file.

### 6.2.1 Load Files

From the TOUGH2Viewer main menu, click the **File->Open structured grid** menu item, and then the "Open structured grid" is displayed (see Fig. 18).

| Open structured grid                         |                  |                        | × |
|--|------------------|------------------------|---|
|  |                  |                        |   |
|  |                  |                        |   |
| .96.80\ExampleData\02_Structured_3D\MESH.dat | Mesh File        |                        |   |
| D\ExampleData\02_Structured_3D\3D_F-im-w.out | Simulated File   |                        |   |
|  | CreateEmptyModel | ExportTOUGH2Viewer.dat |   |
|  | INCON            |                        |   |
| 100%   |                  | Close                  |   |
|  |                  |                        |   |

Fig. 18 - Open Structured grid dialog.

Click the **Mesh File** button to display the Open mesh dialog window and load the "MESH.dat". Click the Open button to start loading the file. When loading is finished, the text box on the left side of the **Mesh File** button will contain the full path of the mesh file.

Click the **Simulated File** button, and then the **Open Simulated** dialog window is displayed. Select the "3D\_F-im-w.out" file and click the **Open** button to load it. The progress bar of the dialog will show the loading advancement.

When the reading is complete, progress bar a 100%, close the dialog by clicking **Close** button. Then, in the main window are shown some geometric information about the model.

### 6.2.2 Export Structured Data to Paraview<sup>1</sup>

Exporting the MESH and the simulation results to Paraview is quite simple using TOUGH2Viewer. loading the simulation results. After the MESH file and click the button ExportTOUGH2Viewer.dat. A file named *tough2viewer.dat* is created in same working folder. Close TOUGH2Viewer and re-start a new session of TOUGH2Viewer. Now choose from the menu the command File->Open unstructured V++ grid ... . Using buttons, load the tough2viewer.dat file, the MESH and the simulation results. Click the Export2VTU button. A set of out\_[i].vtu files is generated in the working folder. You can now open these files with Paraview. See also the chapter 6.4.4 for details.

<sup>&</sup>lt;sup>1</sup> http://www.paraview.org.

| *1)              |             | - 🗆 ×            |
|------------------|-------------|------------------|
|                  | Load last   |                  |
| tough2viewer.dat | File        | 3DPreview        |
| MESH file        | MESH File   |                  |
| Output file      | Tough2 File | CreateEmptyModel |
|                  |             |                  |
|                  | INCON       |                  |
|                  |             | Convert2PLY      |
|                  |             | Export2VTK       |
|                  | Export2CSV  | Export2VTU       |
|                  |             |                  |
|                  |             | Close            |
|                  |             |                  |
|                  |             |                  |

Fig. 19 - Open unstructured V++ grid dialog window.

### 6.2.3 3D block model view

From the main menu, click **View -> 3D block model** menu item. The "3D Block model" dialog window is displayed with the default setting, as shown in Fig. 20.



Fig. 20 - 3D Block model window, top view.

From the "Variable" combo box, select the **T** variable (Temperature). Move the time slider in position 2. Rotate both the model and the color scale using the mouse pointer.

The plot of "3D Block model" dialog window, will be similar to that show in Fig. 21.



Fig. 21 - 3D Block model box showing the Temperature variable at the time step 2.

To split the 3D model Frame, from the "Action" combo box select the **ShiftXY** command, move the mouse on the 3D model frame and left click over a block. The upper part of the model above the clicked block will be shifted as shown in Fig. 22.

| 30 Block model        |                           |               | T 15.0<br>T 325.47 |
|-----------------------|---------------------------|---------------|--------------------|
| Vari                  | able T 0 I                | Action Shifty |                    |
| Appearance Attributes | Block Appearance Variable | Close         |                    |

Fig. 22 - 3D modelFrame horizontally sectioned.

From the Action combo box, choose **ResetPositions** command to reassembly the 3D model Frame, and then select the command **Action->Get2Plot**. Move the mouse on the 3D frame plot and left click on a block to select it.

A Profiles dialog window is displayed, as showed in Fig. 23 and Fig. 24. One can select another variable to plot, acting on the "Variable" combo box, or change the time step by moving the time step slide bar. The "Domain" combo box allows to create a scatter plot of the chose variable, versus one of the Cartesian directions (x, y or z) or versus time.



Fig. 23 – Graph of the pressure versus the x coordinate.



Fig. 24 – Graph of the pressure versus the z coordinate.

For structured grids, is possible to have the background of the plot coloured by the rocktype color scale. Click in option box **Background Material** to obtain the plot as shown in Fig. 25. In order to modify the rocktype scale, open the **Option** dialog window (accessing it from **Tools->Options->tab 3D Model object**).



Fig. 25 – Graph of the pressure versus the z coordinate, with background coloring.

Close the **Profiles** dialog window by clicking the window icon  $\bowtie$  or the **Close** button. Select the **Action->ExpandZ** command to explode the 3D Model Frame of the all layers (see Fig. 26).

| 3D Block model        |  |             |
|-----------------------|--|-------------|
|                       |  |             |
|                       |  |             |
|                       | a na kanakana kana marakana kana kana kana kana kana kana ka | Tazil ke. O |
|                       |  |             |
|                       |  |             |
| Command panel         |  |             |
|                       | Variable T Variable Action FriendWew                         |             |
| Appearance Attributes | Block Appearance Variable                                    |             |

Fig. 26 - ExpandZ command result.

Select both **Action->ResetPositions** and then **Action->QuickInfo** commands. Then click on a block to automatically obtain information about it reported at the bottom of the "3D Block model" dialog window (see Fig. 27).



Fig. 27 - QuickInfo command result, information are printed in a panel at the bottom of the window.

Select the **Action->SetVOI** command to set the coordinates of a volume of interest. When the **SetVOI** dialog window is displayed, select the "**Enable**" check box, click the **Default** button to set a default volume to be hidden (it will be hidden a volume corresponding to half dimension on the three Cartesian direction) and click the **Apply Hide VOI** button. The 3D Block model is modified as shown in Fig. 28.



Fig. 28 - SetVOI function applied to the model.

From the **Block appearance** combo box, select **RockTypes.** The block scale colour is related to the rock type (as shown in Fig. 29).



Fig. 29 - 3D Block model in material color scale.

Note that the color scale frame on the right is not updated with rock type colors. The legend of rock type color is visible in a table present in the Option dialog window. From the main menu select **Tools**-**Option** to display the Option dialog window and click **3D Block model object** tab. To send to the printer the rock type color scale, click the **Print** button.

Close the **3D Block model** and the **Option** dialog by clicking the window icon  $\bowtie$  or the **Close** button.

### 6.2.4 3D Flow Vector visualization

This functionality gives a 3D vector representation of the heat or mass exchange among blocks. From main menu, click **View->3D Flow Vector** and the **3D Flow vector** dialog window is displayed as shown in Fig. 30.



Fig. 30 - Vector representation of the heat flow.

From the **Selection variable** combo box select FHEAT. Move the time slider to "2" and manage the model with usual CAD command.

From the Action combo box, select Get 2D Plot command, then click a vector on the 3D model and then the default Vertical Flow Profiles dialog window is displayed (see Fig. 31).



Fig. 31 - Vertical heat flow profile.

From **Block** combo box, is possible to change the block to be used.

From **Variable** combo box, select a different flow variable and from the **Domain** combo box choose z (versus z axis) or t (versus time)

Close the **Vertical Flow Profile** dialog by clicking the window icon icon or the **Close** button.

Close the **3D** Flow vector dialog by clicking the window icon icon or the Close button.

#### 6.2.5 3D Iso Surface

From TOUGH2Viewer menu bar, click **View->3D IsoSurface** (that is the three-dimensional analogue of the isolines), and then a **3D IsoSurface** dialog window is displayed as shown in Fig. 32.

| 🕌 3D IsoSu | rface      |       |
|------------|------------|-------|
| Variable   | P 💙        |       |
| nx         | 16         |       |
| пу         | 16         |       |
| nz         | 16         |       |
| neigh.     | 10         |       |
| Plot i     | so surface | Close |

Fig. 32 - 3D IsoSurface dialog.

Click Plot iso surface button to obtain an IsoSurface dialog (see Fig. 33).

| 🛓 IsoSurface for P    | at 468235.0 days               |              |
|-----------------------|--------------------------------|--------------|
| I                     |                                |              |
| 40 dq                 |                                |              |
|                       |                                |              |
| -<br>                 |                                |              |
| -                     |                                |              |
| 5                     |                                |              |
| ā                     |                                |              |
|                       | 1900 4900                      |              |
|                       | 🗸 contours 📃 labels 📃 fill     |              |
|                       | 🔲 dashed lines below base      |              |
| interval: 1171413.375 | base: 155866.125               |              |
| P = 155866.125        |                                |              |
| ]                     |                                |              |
| <u></u>               |                                | <b>&gt;</b>  |
| 155866.125            | P = (155866.125, 11870000.001) | 11870000.001 |
| J                     |                                |              |
| Ť<br>O                | 1                              | 1            |
|                       | Properties                     |              |
|                       | Close                          |              |

Fig. 33 - IsoSurface Dialog for pressure and time step 0.

In the **IsoSurface** dialog (the base is the minimum value of the selected variable), rotate the model from top view with usual CAD commands. Move the **slide bar** to set an iso value or move the time step slide bar and observe surface modification. An example is shown in Fig. 34.



Fig. 34 - Dialog window for the pressure IsoSurface.

Close the **IsoSurface for...** dialog by clicking the window icon  $\bowtie$  or the **Close** button. Close the **3D Iso Surface** dialog by clicking the window icon  $\bowtie$  or the **Close** button.

### 6.2.6 2D Contour Plot visualization

This functionality enables to plot the primary variables by means of contour lines.

From main menu, click View->2D Contour plot. A Contour Plot dialog is displayed. From the **Variable** combo box, choose **P** (Pressure), move the slide bar to **2**, select the "**XZ**" item from **Sectioning Plane** combo box. In the **y**= text box, type **500** (to specify the y coordinate of the sectioning plane). Click the **Plot** button and the **Contour Plot** dialog is updated as shown in Fig. 35.



Fig. 35 - 2D Contour Plot for the Pressure (Pa).

Close the **Contour Plot** dialog by clicking the window icon  $\bowtie$  or the **Close** button. To get basic statistic information about the simulated data, from main menu, click **Analysis**-

>Statistics menu item and then the "Statistics" dialog window is displayed (see pag. 18).

Exit form **TOUGH2Viewer** by clicking the window icon **M** or by **File->Exit** menu item.

## 6.3 Unstructured 3D grid model

This tutorial example is related to an unstructured grid model, built using a special GIS GRASS version (Berry et al, 2014) adapted to create locally refined grids.

Please visit http://software.dicam.unibo./tough2gis web pages for further detail.

The example folder "\T2Viewer\ExampleData\03\_Unstructured\_3D" contains the following files and subfolders:

- 3d\_unstruct\_03.out: simulation results
- in.dat: the input file for AMESH
- segmt.dat: output file of AMESH

Subfolder Maps:

•

- Subfolder \"base\_ss" contains the 3D iso contour of the temperature:
  - base\_ss.dbf
  - o base\_ss.prj
  - o base\_ss.qix
  - o base\_ss.shp
  - o base\_ss.shx
  - o base\_ss.xls
  - Subfolder Raster
  - Subfolder "\srtm\_dem" contains gridded ASCII files of the digital elevation model of the topography.

Start **TOUGH2Viewer** (Windows OS) by double clicking the batch file **go.bat** then the main window of TOUGH2Viewer is displayed, as shown in Fig. 36.

| STOUGH2Viewer         |       |  |
|-----------------------|-------|--|
| File View Analysis "  | Fool  |  |
| File Information      |       |  |
| Grid type=            |       |  |
| FileName=             |       |  |
| FilePath=             |       |  |
| n blocks=             |       |  |
| Nodes coordinates:    |       |  |
| ×min=                 | xmax= |  |
| ymin=                 | ymax= |  |
| zmin=                 | zmax= |  |
| Number of time step   | s=    |  |
|                       |       |  |
| University of Bologna | 3     |  |

Fig. 36 - TOUGH2Viewer empty main window

#### 6.3.1 Load Files

From main menu, click the **File->Open unstructured grid** menu item. The **Open unstructured grid** dialog window will be displayed (Fig. 37).

| 🕌 Open unstructured grid |                  |      |           | × |
|--------------------------|------------------|------|-----------|---|
|                          | Load last        |      |           |   |
| FileNameIn               | In File          | ) or | Mesh File | ) |
| FileNameSegmt            | Segmt File       |      |           |   |
| FileNameOut              | Simulated File   |      |           |   |
|                          | CreateEmptyModel |      |           |   |
|                          | Close            | ]    |           |   |
|                          |                  |      |           |   |
| 0%                       |                  |      |           |   |
|                          |                  |      |           |   |

Fig. 37 - Open unstructured grid dialog window

Click the **In File** button to open the **Open In** dialog window and select the file called "in.dat". Click **Open** to start reading this file. Once finished the text box on the left side contains the full path of the file.

Click the **Segmt File** button to open the **Open Segmt** dialog window and select the "segmt.dat" file. Click **Open** to start loading this file. When the loading is finished, the text box on the left side contains the full path of the file.

Click the Simulated File button to open the Open out dialog window and select the "01\_ss\_dir\_01.out" file.

Click **Open** to start loading this file. The progress bar of the **Open unstructured grid** dialog shows the reading process. Close the **Open unstructured grid** dialog by clicking **Close** button to return to the main window.

The main window now shows some geometric information about the loaded model (see Fig. 38).



Fig. 38 - TOUGH2Viewer main window that summarizes some geometric data of the loaded numerical model.

In order to load shapefiles to be included in the 3D Model Frame, from the main menu select the **File**->**Import shapefile** menu item and the **Import shapefile** dialog window is opened (Fig. 39).

| 🛓 Import shapefi | ile       |       | ( |       |
|------------------|-----------|-------|---|-------|
| add new          | Load last |       |   |       |
| ShapeFile        |           | Color |   |       |
|                  |           |       |   |       |
|                  |           |       |   |       |
|                  |           |       |   |       |
|                  |           |       |   |       |
|                  |           |       |   |       |
|                  |           |       |   |       |
|                  |           |       | ( | Close |

Fig. 39 - Import shapefile dialog window.

Click the add new ... button to open the LoadShapeFile dialog window (Fig. 40).

| 🕌 LoadShapeFile |       |
|-----------------|-------|
| Shape File      |       |
| ShowPreview     |       |
| use Z shapes    |       |
| dbf field       |       |
| Import          |       |
|                 |       |
|                 |       |
|                 | Close |

Fig. 40 - Dialog window to load shape files.

Click the **Shape File...** button to display the **Open** dialog window and navigate to the **base\_ss** folder. In particular, select the "**base\_ss.shp**" file (Fig. 41).

| 🛎 Open                 |   |
|------------------------|---|
| Look jn:               | 🔁 base_ss 🕑 🦻 📰 📰   |
| My Recent<br>Documents | ∃ base_ss.shp   |
| Desktop                |   |
| My Documents           |   |
| My Computer            |   |
| 🧐<br>My Network        | File name:     Open       Files of type:     ESRI(tm) Shapefiles (*.shp)     Cancel |

Fig. 41 - Dialog window to select the file to be loaded.

To obtain a 2D preview of the base\_ss.shp file, click **Show Preview** button of the Load Shape File box and the **Shape file preview** window is displayed (Fig. 42).



Fig. 42 - 2D Preview of the base\_ss.shp file

Close the **Shape file preview** window by clicking the window icon  $\bowtie$ . From the **LoadShapeFile** dialog window, select "**Quota**" item in the **dbf field** combo box (to load from a dbf file the elevation quote of the polylines object) (Fig. 43a) and click **Import** button (Fig. 43b).

| 🕌 LoadShapeFile 📃 🗖 🔀 | 🕌 LoadShapeFile 📃 🗖 🔀 |
|-----------------------|-----------------------|
| Shape File            | Shape File            |
| ShowPreview           | ShowPreview           |
| 🔲 use Z shapes        | use Z shapes          |
| cat 💌 dbf field       | Quota 🔽 dbf field     |
| cat<br>Id             | Import                |
| Quota                 |                       |
| Close                 | Close                 |
|                       | a) (b                 |

Fig. 43a, b - LoadShpFile Dialog window

The **Import shapefile** window now will be as shown in Fig. 44. The maximum number of loaded maps depends on the quantity of free RAM memory available.

| 🛓 Import shapefile |       |       |
|--------------------|-------|-------|
| add new Load last  |       |       |
| ShapeFile          | Color |       |
| base_ss.shp        |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       |       |
|                    |       | Close |

Fig. 44 - Import shapefile window. The table resume imported shape files.

By double clicking the **color** bar near the file name, the **Choose a color...** window dialog window is displayed to change the color of polylines (Fig. 45). Choose a color to plot the curve of the shape map and click **OK**, then close the **LoadShapeFile** window by clicking the window icon is or the **Close** button.

| 🛎 Choose a color   | × |
|--|---|
| Swatches HSB RGB   |   |
|  |   |
| Preview  |   |
| Image: A state of the state |   |
| Sample Text Sample Text  |   |
| OK Cancel <u>R</u> eset  |   |

Fig. 45 – "Choose a color ..." dialog window window.

Close the **Import shapefile** dialog window by clicking the window icon 🔀 or the **Close** button.

### 6.3.2 3D Block model view

From TOUGH2Viewer menu bar, click **View -> 3D block model** menu item and the **3D Block model** dialog window display, as shown in Fig. 46.



Fig. 46 - Top view of the 3D Block model.

The isolines and surface representing the base\_ss.shp loaded in the previous step is now merged in the model and can be showed.

One can rotate, zoom, pan the model etc. using the mouse. To change variable to be showed, select it from **Variable** combo box. To change the time step, move the slide bar and automatically the plot will be update.

From the Action combo box, select SetVOI. A SetVOI dialog window is displayed. In the panel Hide VOI, check the Enable checkbox, click both Default and Apply Hide VOI buttons (Fig. 47).
| 🕌 SetVO | l           |      |                |       |
|---------|-------------|------|----------------|-------|
|         | Of Interest |      |                |       |
| ×min    | 1701500.0   | xmax | 1726500.0      |       |
| ymin    | 4732500.0   | ymax | 4759500.0      |       |
| zmin    | -3850.0     | zmax | 1700.0005      |       |
|         | Reset       |      | Apply VOI      |       |
| HideVOI |             |      |                |       |
| 📃 Enab  | le          |      |                |       |
| ×min    | xmin        | xmax | xmax           |       |
| ymin    | ymin        | ymax | ymax           |       |
| zmin    | zmin        | zmax | zmax           |       |
|         | Default     | C    | Apply Hide VOI | Close |

Fig. 47 - SetVOI dialog window.

Close the **SetVOI** dialog by clicking the window icon  $\bowtie$  or the **Close** button.

Is possible to rotate the view and minimize/enlarge the 3D frame by clicking the up black arrows (right-oriented arrow to minimize, left-oriented arrow to enlarge). The view of the model is now as shown in Fig. 48.

To obtain block information, choose **Action->QuickInfo**, then click a block on the 3D frame. At the bottom of the dialog window, a set of information about the selected block will be displayed (Fig. 48, (a)). This information will be automatically update when another variable or time step is selected (Fig. 48, (b)).



Fig. 48 - (a) 3D model partially showed and block selected (white block); (b) information related to the selected block.

From the **Action** combo box, select **FindBlocks** and the **Find Blocks** dialog window is displayed (Fig. 49). From the combo box, select a specific block (by the TOUGH2 name) and automatically in the **Block information** panel some information about it are showed and in the 3D model frame it will be highlighted.

To unselect the block, click **unselect** button. Close the **Find Blocks** dialog by clicking the window icon  $\bowtie$  or the **Close** button.

| 🛓 Find Blocks   |                   |           |       |
|-----------------|-------------------|-----------|-------|
| Block Selection | Block information |           |       |
| A31 1 🗸         | BlockName=        | A31 1     |       |
|                 | Xo=               | 1711323.4 |       |
|                 | Yo=               | 4748147.5 |       |
| AAAAA search    | Zo=               | 1700.0005 |       |
|                 | Rocktype=         | ATMOS     |       |
| unselect        |                   |           |       |
|                 |                   |           | Close |

Fig. 49 - Find Block dialog window.

From the **Action** combo box, select **SnapShot** to display a **SnapShot Preview** dialog window that contains an image of the three-dimensional model (Fig. 50). With the **File->Save as...** menu item is possible to save the image (in png format) or send it directly to the printer by **File->print** menu item.

Close the **SnapShot** dialog window by clicking the window icon **M** or via the **File->Exit** menu item.



Fig. 50 - Snapshot Preview window dialog window.

To repaint each block in material scale color (Fig. 51), from the **Action** combo box of the **3D Block model** dialog window, execute the following commands:

- ResetPositions;
- FrontView;
- SetVOI and in the setVOI dialog window uncheck Enable check box and close setVOI dialog window;



From Block Appearance of the 3D Block model dialog window, select RockType.

Fig. 51 - 3D Block Model front view. Material color scale.

From main menu, choose **Tools-> Options**, then click **3D Block model object** tab to open the Options dialog window (Fig. 52).

| 🕌 Options                  |                          |                       |               |             |       |
|----------------------------|--------------------------|-----------------------|---------------|-------------|-------|
| Visualization Filter 3D Bl | ock model Object 3D Flow | model Misc. Skins     | Plot Format   |             | 1     |
| Appearance                 |                          | Block Stretch         |               |             |       |
| Light one                  |                          | Reduce Block Factor ( | 0.5-1.0) 0.85 | Apply       |       |
| Light two                  | Thoose Background        | Z Stretch Factor      | 1.0           | Apply       |       |
| Ambient light              |                          |                       |               |             |       |
| Material                   | Color                    |                       | Visible       |             |       |
| ATMOS                      |                          |                       |               |             |       |
| CAPRO<br>SHOL1             |                          |                       |               |             |       |
| SHAL2                      |                          |                       |               |             |       |
| SPIMP                      |                          |                       |               |             |       |
| SPLIQ                      |                          |                       |               |             |       |
| VOLCA                      |                          |                       |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               | Print       |       |
| Shapefile                  | Color                    | Contour line visi     | ble Surf      | ace visible |       |
| base_ss.shp                |                          | ✓                     |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               |             |       |
|                            |                          |                       |               |             | Close |

Fig. 52 – "Options" dialog window, "3D Block model object" tab.

To obtain the view showed in Fig. 45, in the "Material" table of **3D Block model Object** tab, uncheck the check box of column **Visible** for:

ATMOS, CAPRO, SHAL1, SHAL2, VOLCA as show in Fig. 53. Only the materials SPIMP and SPLIQ are kept visible.

| Subjections   | 3D Block model Ob | ject 3D Flow mo | del Misc. Skins I                                    | Plot Format         |                |       |
|---|-------------------|-----------------|--|---------------------|----------------|-------|
| Appearance<br>Light one<br>Light two<br>Ambient light                   | Choose Backg      | round Z SI      | ck Stretch<br>Juce Block Factor (0.<br>tretch Factor | .5-1.0) ).85<br>1.0 | Apply<br>Apply |       |
| Material<br>ATMOS<br>CAPRO<br>SHAL1<br>SHAL2<br>SPIMP<br>SPLIQ<br>VOLCA |                   | Color           |  | Visible             |                |       |
| Shapefile   | Color             |                 | Contour line visib                                   | le Su               | Print          |       |
| base_ss.shp   |                   |                 | V  |                     |                |       |
|   |                   |                 |  |                     |                | Close |

Fig. 53 - Options dialog "3D Block model object" tab, with modified parameters.

To set not visible the contour line or the surface of shapefiles, uncheck the respective check box in the **3D Block model Object** tab. Close the Options windows using the window icon  $\bowtie$ , or the **Close** button. **The 3D Block model** view now will appear as showed in Fig. 54.



Fig. 54 - 3D Block model.

In the **Options** dialog window, **3D Block model Object** tab, restore ATMOS, CAPRO, SHAL1, SHAL2, VOLCA again visible.

In the **3D Block model**, from the **Action** combo box select **Get2DPlot** command. Click a block in the 3D frame and a **Profiles** dialog window is displayed.

From the time slider menu select the time step "6". The graph will be update as shown in Fig. 55.



Fig. 55 - Profiles dialog which shows the pressure values along z axis.

Close the **Profiles** dialog window by clicking the *indows* icon or the **Close** button.

In the **Options** dialog window, click on the **Visualization Filter** tab, select the **T** variable. In the **min** text box, type "270.0" and click the **setNewValue** button, and select the **HideOutOfRange** check box. In this way only blocks with temperature value between 270.0 and 291.01 °C are visible, note that also the colour scale, on the right frame, has changed as shown in Fig. 56.

In the **3D Block model** window, select **T** from **Variable** combo box and move the time slider at position "6-th" (last time step present in this simulation output file).



Fig. 56 - Bottom filtered view of the 3D model with modified color scale.

Close the **3D block Model** by clicking the X windows icon or the **Close** button.

## 6.3.3 3D Flow Vector visualization

This functionality gives a 3D vector representation of the heat or mass exchange among blocks. Select the **View->3D Flow Vector** menu item. A **3D Flow Vector** window opens, showing the default variable FHEAT, as shown in Fig. 57.



Fig. 57 - 3D Flow vector default view.

From the Variable combo box, select **Vel(GAS)** item and move the time slider to **1**. With the usual CAD command zoom and rotate the model in the desiderated position (Fig. 58).



Fig. 58 - 3D Flow model at the time step 1 for the variable VEL(GAS).

Close the **Flow profile** window by clicking the windows icon or the **Close** button. Close the **3D Flow vector** window by clicking the windows icon or the **Close** button.

## 6.3.4 3D Iso Surface

Select the View->3D Iso Surface menu item.

Open a **3D** Iso Surface dialog (Fig. 59) and from the Variable combo box, select **T** (default is P). Leave other parameters as default and click **Plot iso surface** button. Wait few seconds to complete the interpolation process, and then a new **IsoSurface** window opens to plot the selected variable.

| 🕌 3D IsoSurfa | ace     |       |
|---------------|---------|-------|
| Variable P    | *       |       |
| nx            | 16      |       |
| пу            | 16      |       |
| nz            | 16      |       |
| neigh.        | 10      |       |
| Plot iso      | surface | Close |

Fig. 59 - 3D IsoSurface dialog window.

In this window, move the first continuous **slider** to 270 °C. The plot windows will appear as shown in Fig 52. To see the evolution of isosurface over time steps, move the time slider located under continuous slider. Click the **Properties** button to change colour background, to switch from parallel to perspective view, to change axis colour or to hide the thin box.



Fig. 60 - Isosurface for T=270°C, time step "6".

Close the **IsoSurface for T** ... and the **3D Isosurface** window by clicking the  $\bowtie$  windows icon or the **Close** button.

## 6.3.5 2D Contour map

Select the View->2D Contour map menu item and a 2D Contour plot window will open. In the 2D Contour plot window, set the Sectioning plane combo box to XZ, and type "4745000" (vertical XZ section at y=4745000 m), move the time slider at position "6-th" (last time step present in this simulation output file) and click the Plot button. A Contour Plot window will be displayed as shown in Fig. 61.



Fig. 61 – Temperature isolines contour map.

After having adjusted the parameter of plotting, click the **Plot** button to update the graph. Close the **2D Contour plot** window by clicking the **X** windows icon or the **Close** button.

## 6.3.6 Statistics

Click the **Analysis-> Statistics** menu item and then **Statistics** dialog window opens. See paragraph 6.1.5 for details about **Statistics** dialog.

Exit form **TOUGH2Viewer** by clicking the window icon **S** or by **File->Exit** menu item.

## 6.4 Voronoi 3D grid model

This example is related to a Voronoi 3D unstructured grid model, built using VORO2MESH (Bonduà et al., 2017) to create full Voronoi 3D grid. This grid is also a Central Voronoi Tessellation (CVT). The example folder "\T2Viewer\ExampleData\04\_voronoi\_3D\"contains the following files:

- MESH: the classical TOUGH MESH
- o tough2viewer.dat: the geometry file, as generated by VORO2MESH;
- o voronoi3D.out: the simulation output results of TOUGH simulation run.

Start **TOUGH2Viewer** (Windows OS) by double clicking the batch file **go.bat** then the main window of TOUGH2Viewer is displayed, as shown in Fig. 62.

| <u>لا</u>                                   | TOUGH2Viewer | - 🗆 × |  |
|---|--------------|-------|--|
| File View Analysi                           | s Tool       |       |  |
| File Information<br>Grid type=<br>FileName= |              |       |  |
| FilePath=                                   |              |       |  |
| n blocks=<br>Nodes coordinat                | es:          |       |  |
| xmin=                                       | xmax=        |       |  |
| zmin=                                       | zmax=        |       |  |
| Number of time :                            | steps=       |       |  |
| University of Bold                          | ogna         |       |  |

Fig. 62 - TOUGH2Viewer empty main window.

## 6.4.1 Load Files

From main menu, click the **File->Open unstructured V++ grid** menu item. The **Open unstructured V++ grid** dialog window will be displayed (Fig. 63).

| 🛓 Open unstruct  | tured V++ grid | - 🗆 ×            |
|------------------|----------------|------------------|
|                  | Load last      |                  |
| tough2viewer.dat | File           | 3DPreview        |
| MESH file        | MESH File      |                  |
| Output file      | Tough2 File    | CreateEmptyModel |
|                  |                |                  |
|                  | INCON          |                  |
|                  |                | Convert2PLV      |
|                  |                |                  |
|                  |                | Export2VTK       |
|                  | Export2CSV     | Export2VTU       |
|                  |                |                  |
|                  |                | Close            |
|                  |                | Close            |

Fig. 63 – Input unstructured grid window

Click the **File** button to open the **tough2viewer.dat** dialog window and select the file called "tough2viewer.dat" from the working folder.

Click **Open** to start reading this file. Once finished is possible to visualize a preview by clicking the **3DPreview** button on the right.

Click the **MESH File** button to open the **Open MESH** dialog window and select the "MESH" file in the same folder.

Click **Open** to start loading this file. Click the **Simulated File** button to open the **Open out** dialog window and select the "**voronoi.out**" file.

Click **Open** to start loading this file. The progress bar of the **Open unstructured V++ grid** dialog shows the reading process. Close the **Open unstructured V++ grid** dialog by clicking **Close** button to return to the main window.

The main window now shows some geometric information about the loaded model (see Fig. 38).

| <u></u> |                         | TOUGH2Viewer                         | - 🗆 🗙               |
|---------|-------------------------|--------------------------------------|---------------------|
| Fil     | e View Analysis Tool    |                                      |                     |
|         | File Information        |                                      |                     |
|         | Grid type=              | 3D - xyz - Radial grid               |                     |
|         | FileName =              | voronoi3D.out                        |                     |
|         | FilePath=               | D:\T2Viewer\T2Viewer_v0.96.7\Example | Data\04_Voronoi_3D\ |
|         | n blocks= 10            | 32                                   |                     |
|         | Nodes coordinates:      |                                      |                     |
|         | xmin= 0.0               | xmax= 1000.0005                      |                     |
|         | ymin= 0.0               | ymax= 1000.0005                      |                     |
|         | zmin= -1000.0005        | zmax= 0.0                            |                     |
|         | Number of time steps= 1 | L                                    |                     |
|         |                         |                                      |                     |
| U       | niversity of Bologna    |                                      |                     |

Fig. 64 – The main window

## 6.4.2 3D Block model view

From TOUGH2Viewer menu bar, click **View -> 3D block model** menu item and the **3D Block model** dialog window display, as shown in Fig. 65.



Fig. 65 - Top view of the 3D Block model.

Move the variable combo box to  ${\bf SG}$  (Saturation of Gas). Rotate and change the time step progressively.

Visualization can appear as follow in Fig. 66.



Fig. 66 – View of the SG thermodynamic variables (3D Block model).

Explore the model with the command as explained in the previous chapters.

## 6.4.3 Prepare GENER file

In this paragraph, by using TOUGH2Viewer is possible to select the blocks that will be used as GENER blocks int TOUGH simulations.

From the Action dropdown menu select the **MultipleSelection** Command.

As shown in Fig. 67, select two top opposite blocks of the grid by clicking on it.



Fig. 67 - MultipleSelection command: a set of blocks that can be selected for further editing or exporting

Select from the Action dropdown menu the AdvanceBlockSelection, and then click on the button Open modify Selection...

| 🛓 Properties modif  | fier          | _     |   | ×    |
|---------------------|---------------|-------|---|------|
|                     |               |       |   |      |
| Rocktype            | 1 ~           | Apply |   |      |
| New Rocktype        | ABCDE         | Apply |   |      |
| Volume              | 1.0E55        | Apply |   |      |
| Load Selection      |               |       |   |      |
|                     | String to add | d     |   |      |
| SaveThisSelection . |               |       |   |      |
|                     | HOT##         |       |   |      |
| ExportThisSelection |               |       |   |      |
| ExportTheModifiedG  | rid           |       | C | lose |

Fig. 68 – Properties modifier dialog window. With the current block selection, is possible to assign an existing rocktype (button rocktype) or to create and assign a new rocktype (button New RockType).

The properties modifier dialog window will shown (Fig. 68). Click on **ExportThisSelection** and choose a filename, for example "generblocks". An ASCII file will be created as shown in Fig. 69.

```
      ELEME - MESH File for D:\D\T2Viewer\ExampleData\04_Voronoi_3D\twoblocks.dat genera

      A11 1
      * 1 8.855e+05
      5.669e+01 4.559e+01-4.190e+01

      A41 1
      * 1 8.687e+05
      9.581e+02 9.347e+02-4.114e+01

      CONNE
```

Fig. 69 - The generated ASCII file

Remove all unwanted information and create your GENER file by using a text editor (Fig. 70).

| GENE | ER5  |   |   |      |       |       |
|------|------|---|---|------|-------|-------|
| A11  | 1inj | 1 | 1 | MASS | 3.75  | 8.0E4 |
| A41  | 1PRO | 1 | 1 | MASS | -3.75 |       |

Fig. 70 – The modified GENER file

#### **INCON** generation

Before creating an INCON file, is necessary to load a previous INCON or SAVE file as created, for example, by VORO2MESH or by a dummy run of TOUGH.

Load the INCON from file by the **Open Unstructured V++ grid...** dialog window.

Press the **Generate INCON** button. A new dialog window will be shown. From the variable selector select INCON\_0 and then press the **add** button. Repeat the previous step up to the INCON\_3 variable. Select from the INCON VARIABLES selector the INCON\_0 variable and update the plot by pressing UpdatePlot. The Dialog will now have the aspect of Fig. 71.



Fig. 71 – INCON generator dialog window.

Set your value of INCON\_0 (Pressure in this example) as 3.0E6 Pa and click on Preview button. In The new graph will be updated as shown in Fig. 72. Click on the **Apply** button to apply the changes.



Fig. 72 – INCON generator dialog window preview.

Click on **Apply**. Repeat all steps for the other INCON variables. When finished, move to the **Write Out tab**, and click on update preview, as shown in Fig. 73.

| are INCON Write OUT         re INCON to a file         rmat Strings:         OCKNAME (S CHARS)+       \n         CON VARIABLES       \$19e         D OF LINE       \n         source+o6       3.500000e+03       1.070000e+01       2.400000e+02         36 1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38 1       3.00000e+06  | are INCON Write OUT         the INCON to a file         armat Strings:         OCKNAME (S CHARS)+       \n         CON VARIABLES       \n         b) OF LINE       \n         eview:       Update Preview         78       1         3.000000e+06       3.500000e-03         3.00000e+06       3.50000e-03         3.00000e+06       3.50000e-03       1.07000e+01         2.40000e+06       3.50000e-03       1.07000e+01         3.00000e+06       3.50000e-03       1.07000e+01         3.00000e+06       3.50000e-03       1.07000e+01         3.00000e+06       3.50000e-03       1.070000e+01         3.000   | are INCON [Write OUT]         the INCON to a file         mmat Strings:         OCKNAME (S CHARS)+       n         0 OF LINE       1         10 OF LINE       1         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03       1.070000+01       2.400000+02         10       3.000000+06       3.500000+03   | ICON (  | Generator     |              |              |                |  |  |  |  |  | - |  |
|--|---|---|---------|---------------|--------------|--------------|----------------|--|--|--|--|--|---|--|
| ale InCON to a file         rmat Strings:         OCKNAME (S CHARS)+ \n         0 OF LINE         0 OF LINE         view:       Update Preview         28 1       3.000000+06       3.500000+03         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.1000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.000000+06       3.500000+03       1.070000+01         3.  | aide JRCUN wine GOT         wine INCON a file         wine Strings:         OCKNAME (S CHARS)+         In         DO OF LINE         No         30.000000+06         3.5000000+06         3.5000000+06         3.000000+06  | aid BICUN TWIE COM         aid BICUN TWIE COM         mmat Strings:         OCKNAME (S CHARS)+       in         con VARIABLES       19e         bit OF LINE       in         28 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02       in         3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02       in         3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02       in         3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02       in         3.1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         3.1       3.00000e+06   | DEC TH  | CON Write OUT |              |              |                |  |  |  |  |  |   |  |
| rmat Strings:         OCKNAME (5 CHARS)+       \n         CON VARIABLES       19e         D OF LINE       \n         eview:       Update Preview         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06 <td>rmat Strings:<br/>OCKNAME (5 CHARS)+ \n<br/>CON VARIABLES \19e<br/>DO F LINE \n<br/>eview: Update Preview<br/>78 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>78 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>79 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br/>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br/>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br/>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>70 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br/>70 1 3.00000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br/>70 1 3 1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1</td> <td>armat Strings:         COKNAME (S CHARS)+       n         CON VARIABLES       19e         b) OF LINE       n         eview:       Update Preview         78 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         89 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         89 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         80 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 3       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000-03       1.070</td> <td></td> <td>N to a file</td> <td></td> | rmat Strings:<br>OCKNAME (5 CHARS)+ \n<br>CON VARIABLES \19e<br>DO F LINE \n<br>eview: Update Preview<br>78 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>78 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>79 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br>79 1 3.00000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>70 1 3.00000e+06 3.500000e+03 1.070000e+01 2.40000e+02<br>70 1 3.00000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>70 1 3.000000e+06 3.500000e+03 1.070000e+01 2.400000e+02<br>70 1 3 1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1   | armat Strings:         COKNAME (S CHARS)+       n         CON VARIABLES       19e         b) OF LINE       n         eview:       Update Preview         78 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         89 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         89 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         80 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 3       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81 1       3.000000+06       3.500000-03       1.070  |         | N to a file   |              |              |                |  |  |  |  |  |   |  |
| rmat Strings:         OOKNAME (S CHARS)+       \n         CON VARIABLES       \n         D OF LINE       \n         eview:       Update Preview         7a       3.000000+06       3.500000+03       1.070000+01       2.4000000+02         7a       3.000000+06       3.500000+03       1.070000+01       2.4000000+02         7a       3.000000+06       3.500000+03       1.070000+01       2.400000+02         7a       3.000000+06       3.500000+03       1.070000+01       2  | smal String::         OCKNAME (\$ CHAR\$)+       \n         CON VARIABLES       \$19e         DO OF LINE       \n         ever:       Update Preview         72       1       0.00000e+06       3.500000e-03       1.070000e+01       2.400000e+02         81       3.00000e+06       3.500000e-03       1.070000e+01       2.400000e+02       n         82       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         83       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         84       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         85       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         86       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         87       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         88       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02       n         89       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02       n   | mmat String::         OCKNAME (S CHARS)+       \n         CON VARIABLES       919         DO F LINE       \n         eview:       Update Preview         Ta 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.00000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         30 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         30 1       3.000000e+06   | te nico | on to a me    |              |              |                |  |  |  |  |  |   |  |
| Trad Strings:         OOKNAMME (S CHARS)+       \n         CON VARIABLES       \$19e         D OF LINE       \n         seview:       Update Preview         75       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         81       3.000000e+06       3.50000e+03       1.070000e+01       2.400000e+02         81       3.000000e+06       3.500000e+03<   | armat Strings:         OCKNAME (S CHARS)+       \n         CON VARIABLES       \$19e         b) O F LINE       \n         2000000+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         32       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         32.00000e+06       3.50000e-03  | and Strings:         OCKNAME (S CHARS)+       n         eVew:       •19e         b) OF LINE       n         eview:       •Update Preview         71       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         30       1.070000+01       2.400000+02       1.070000+02       1.070000+02       1.070000+02         30       1.070000+03       1.070000+01       2.400000+02   |         |               |              |              |                |  |  |  |  |  |   |  |
| OOCKNAME (S CHARS)+<br>CON VARIABLES       \n         0 OF LINE       \n         view:       Update Preview         78       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         89       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81       3.000000+06       3.500000+03       1.070000+01       2.400000+02         81       3.000000+06       3.500000+0  | OOCKNAME (S CHARS)+<br>(n       (n         CON VARIABLES       19e         DO OF LINE       (n         2000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         78 1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         81 3       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         81 3       3.00000e+06       3.50000e  | OOCKNAME (S CHARS)+<br>CON VARIABLES       19e         DID OF LINE       19e         2000000+06       3.500000+03       1.070000+01       2.400000+02         21       3.000000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02         28       1       3.00000+06       3.500000+03       1.070000+01       2.400000+02  | rmat S  | Strings:      |              |              |                |  |  |  |  |  |   |  |
| CON VARIABLES       19e         D OF LINE       \n         eview:       Update Preview         Tal       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.0       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.0       3.00000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.0       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.0       3.000000e+06  | CON VARIABLES       19e         ID OF LINE       \n         eview:       Update Preview         78       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         88       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         98       1       3.000  | CON VARIABLES       919e         ID OF LINE       In         eview:       Update Preview         75 1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.00000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.5000000+03       1.070000+01       2.4000   | OCKNA   | ME (5 CHARS)+ | \n           |              |                |  |  |  |  |  |   |  |
| DO OF LINE       \n         view:       Update Preview         3.000000+06       3.500000+03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.0       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.0       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.0       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.0       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.1       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.1       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.1       3.000000+06       3.500000+03       1.070000+01       2.400000+02       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02       1       1 <td>DO OF LINE       \n         eview:       Update Preview         72       3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       1.070000+01       2.400000+02       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32       <td< td=""><td>DO OF LINE       \n         eview:       Update Preview         78       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         88       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.000000e+06       3.500000e-03</td><td></td><td>ARTABLES</td><td>\$19e</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<></td>  | DO OF LINE       \n         eview:       Update Preview         72       3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         38       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       1.070000+01       2.400000+02       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32       1.000000+06       3.500000-03       1.070000+01       2.400000+02         32 <td< td=""><td>DO OF LINE       \n         eview:       Update Preview         78       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         88       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.000000e+06       3.500000e-03</td><td></td><td>ARTABLES</td><td>\$19e</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>  | DO OF LINE       \n         eview:       Update Preview         78       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         88       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         98       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         98       1       3.000000e+06       3.500000e-03   |         | ARTABLES      | \$19e        |              |                |  |  |  |  |  |   |  |
| DO OF LINE       In         eview:       Update Preview         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.100000+06       3.500000+03       1.070000+01       2.400000+02         3.1000000+06       3.500000+03       1.070000+01       2.400000+02         3.1000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02         3.000000+06       3.500000+03       1.070000+01       2.400000+02  | DO F LINE       Va         eview:       Update Preview         71       3.000000+06       3.500000-03       1.070000+01       2.400000+02         81       3.000000+06       3.500000-03       1.070000+01       2.400000+02         81       3.000000+06       3.500000-03       1.070000+01       2.400000+02         82       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         83       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         84       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         85       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         85       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         86       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         86       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         81       3.000000+06       3.500000-03       1.070000+01       2.400000+02       2.400000+02         82       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02 <t< td=""><td>DO F LINE       Ya         eview:       Update Preview         78       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         89       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         89       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         80       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         81       3.000000+06       3.500000-03       1.070000+01       2.400000+02       V         82       1       3.000000+06       3.500000-03       1.070000+01       2</td><td></td><td></td><td>\</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>  | DO F LINE       Ya         eview:       Update Preview         78       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         88       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         89       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         89       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         80       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         81       3.000000+06       3.500000-03       1.070000+01       2.400000+02       V         82       1       3.000000+06       3.500000-03       1.070000+01       2  |         |               | \            |              |                |  |  |  |  |  |   |  |
| Perview:       Update Preview         1       3.00000e+06       3.50000e+03       1.070000e+01       2.400000e+02         16       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         16       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         17       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         18       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         18  | aview:       Update Preview         1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         19       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         19       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         19       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         19   | aview:       Update Preview         1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         18       1       3.000000+06   | D OF L  | LINE          | \n           |              |                |  |  |  |  |  |   |  |
| 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         381       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         382       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         381       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         30       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         30       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02      <   | 3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.00000e+06 <td< td=""><td>3.000000e+06       3.50000e+03       1.070000e+01       2.400000e+02         78       1       3.00000e+06       3.50000e+03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         30       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         30<!--</td--><td>eview.</td><td>Undate Pr</td><td>eview</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td></td<>   | 3.000000e+06       3.50000e+03       1.070000e+01       2.400000e+02         78       1       3.00000e+06       3.50000e+03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.40000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         38       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         30       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         30 </td <td>eview.</td> <td>Undate Pr</td> <td>eview</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>                                  | eview.  | Undate Pr     | eview        |              |                |  |  |  |  |  |   |  |
| 3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02 <td>3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02<td>3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06<!--</td--><td>cilen.</td><td>opudern</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td></td>   | 3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02 <td>3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06<!--</td--><td>cilen.</td><td>opudern</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td>  | 3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000+03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06       3.500000-03       1.070000+01       2.400000+02          3.000000+06 </td <td>cilen.</td> <td>opudern</td> <td></td>   | cilen.  | opudern       |              |              |                |  |  |  |  |  |   |  |
| 3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.1000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.1000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.1000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.   | 3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         38       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         38       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         38       1       3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         31       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         32       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         32       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         38       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         32       1       3.000000e+06       3.500000e-03       1.07000e+01 </td <td>3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02</td> <td>781</td> <td>3.00000e+06</td> <td>3.50000e-03</td> <td>1.070000e+01</td> <td>2.400000e+02 🔨</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>                                       | 3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02   | 781     | 3.00000e+06   | 3.50000e-03  | 1.070000e+01 | 2.400000e+02 🔨 |  |  |  |  |  |   |  |
| 3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+   | 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01 <td>3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02</td> <td></td> <td>3.0000000+06</td> <td>3.5000000-03</td> <td>1.070000e+01</td> <td>2.400000e+02</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> | 3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02         3.000000+06       3.500000-03       1.070000+01       2.400000+02   |         | 3.0000000+06  | 3.5000000-03 | 1.070000e+01 | 2.400000e+02   |  |  |  |  |  |   |  |
| 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.10       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02  | 3:000000e+06       3:500000e+03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:40000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:40000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:40000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:40000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.070000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.070000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.070000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.070000e+01       2:400000e+02         3:000000e+06       3:500000e-03       1.07000e+  | 30       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         31       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02         32       3.000000+06       3.500000-03       1.070000+01       2.400000+02 <td>5B 1</td> <td>3.00000e+06</td> <td>3.500000e-03</td> <td>1.070000e+01</td> <td>2.400000+02</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> | 5B 1    | 3.00000e+06   | 3.500000e-03 | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
| AB 1       3.000000e+06       3.500000e+03       1.07000e+01       2.400000e+02         B1       3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         B2 1       3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         B2 1       3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2 1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2 1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2 1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B3 1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02  | AB       1         3.000000+06       3.500000+03       1.070000+01       2.400000+02         BE       1       3.000000+06       3.500000-03       1.070000+01       2.400000+02         BE       1       3.000000+06  | AB       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         AB       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         AB       1       3.000000+06       3.500000+03       1.070000+01       2.400000+02         BA       1       3.000000+06       3.500000+  | 9B 1    | 3.000000+06   | 3.500000e-03 | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
| 38       1       3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         38       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         30       3.000000e+06       3.500000e-03   | BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         CB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         CD 2       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         CD 3       0.00000e+01       2.400000e+02       COUNDE+02       COUNDE+02         Select a file name for saving:       Choose File to save as       V   | BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         BB 1       3.000000e+06       3.5000   | AB 1    | 3,000000e+06  | 3.500000e-03 | 1.070000e+01 | 2.400000e+02   |  |  |  |  |  |   |  |
| 3.000000e+06       3.50000e+03       1.070000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02   | 3.000000e+06       3.50000e+03       1.070000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         V       V       V       V       V       V  | 3.000000e+06       3.50000e+03       1.070000e+01       2.40000e+02         3.000000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.40000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2       1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B2       1       3.00000e+06       3.50000e-03       1.07000e+01       2.400000e+02         B2 <t< td=""><td>BB 1</td><td>2 000000-000</td><td>2 500000- 02</td><td>1.070000-001</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>                           | BB 1    | 2 000000-000  | 2 500000- 02 | 1.070000-001 |                |  |  |  |  |  |   |  |
| 3.000000e+06 3.50000e-03 1.070000e+01 2.400000e+02<br>3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>FE 1<br>3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>HE 1<br>3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>V  | 3.000000e+06       3.50000e-03       1.070000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.07000e+01       2.400000e+02         3.00       3.500000e-03       1.07000e+01       2.400000e+02         3.00       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         W       Select a file name for saving:       Choose File to save as   | 3.000000e+06       3.50000e-03       1.070000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.40000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3E 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         W       W       W       W       W   | CB 1    | 3.00000000+00 | 3.5000008-03 | 1.0700000+01 | 2.400006+02    |  |  |  |  |  |   |  |
| 3.000000e+06 3.50000e-03 1.070000e+01 2.400000e+02<br>30.00000e+06 3.50000e-03 1.070000e+01 2.400000e+02<br>FB 1 3.000000e+06 3.50000e-03 1.070000e+01 2.400000e+02<br>B 1 3.000000e+06 3.50000e-03 1.070000e+01 2.400000e+02<br>FB 1 3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>FB 1 S.000000e+06 S.500000e-03 S.50000e-03 S.50000e+01 S.400000e+02<br>SE 1 S.000000e+06 S.500000e-03 S.50000e+01 S.400000e+02 S.4000000e+02 S.40000   | 3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         BB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         BB 1       Select a file name for saving:       Choose File to save as  | 3.000000e+06       3.500000e+03       1.070000e+01       2.400000e+02         BE 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.00       3.500000e-03       1.070000e+01       2.400000e+02         3.1       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         B1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         B2       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         W       V       V       V       V   | DB 1    | 3.000000e+06  | 3.50000e-03  | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
| 3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         7B 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3B 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         1B 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         IB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         IB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02  | 3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         HB       1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         V       V       V       V       V   | 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         HB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         W       W       W       W       W         Select a file name for saving:       Choose File to save as       V  | RR 1    | 3.000000e+06  | 3.50000e-03  | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
| 3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         B1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         B1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         V       V  | 3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         B1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         IB1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         V       V       V       V  | 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         IB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         IB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         V       V       V       V   |         | 3.000000e+06  | 3.50000e-03  | 1.070000e+01 | 2.400000e+02   |  |  |  |  |  |   |  |
| 3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>HB 1 3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02<br>V   | 38       1       3.000000e+06       3.50000e-03       1.07000e+01       2.400000e+02         IB       1       3.000000e+06       3.50000e-03       1.070000e+01       2.400000e+02         V       V       V       V         Select a file name for saving:       Choose File to save as  | 3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         IB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         ISelect a file name for saving:       Choose File to save as   | .в I    | 3.00000e+06   | 3.500000e-03 | 1.070000e+01 | 2.400000e+02   |  |  |  |  |  |   |  |
| HB 1<br>3.000000e+06 3.500000e-03 1.070000e+01 2.400000e+02  | HB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         Select a file name for saving:       Choose File to save as  | HB 1       3.000000e+06       3.500000e-03       1.070000e+01       2.400000e+02         V       V         Select a file name for saving:       Choose File to save as  | 3B 1    | 3.000000e+06  | 3.5000000-03 | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
| v  | Select a file name for saving: Choose File to save as   | Select a file name for saving: Choose File to save as   | IB 1    | 3.000000e+06  | 3.500000e-03 | 1.070000e+01 | 2.400000+02    |  |  |  |  |  |   |  |
|  | Select a file name for saving: Choose File to save as   | Select a file name for saving: Choose File to save as   |         |               |              |              | ~              |  |  |  |  |  |   |  |
|  | Select a file name for saving: Choose File to save as   | Select a file name for saving: Choose File to save as   |         |               |              |              |                |  |  |  |  |  |   |  |
|  |   |   |         |               |              |              |                |  |  |  |  |  |   |  |
|  |   |   |         |               |              |              |                |  |  |  |  |  |   |  |
|  |   |   |         |               |              |              |                |  |  |  |  |  |   |  |
|  |   |   |         |               |              |              |                |  |  |  |  |  |   |  |

Fig. 73 - INCON generator dialog window -write out tab preview

To export the INCON data press on the Choose File to save as... and insert the output filename.

## 6.4.4 Export data to Paraview

To export the model in a file format readable using Paraview, from the main menu, click the **File**->**Open unstructured V++ grid** menu item.

The **Open unstructured V++ grid** dialog window will be displayed (Fig. 63). Click the command button **Export2VTU.** A set of files (one for each time step) will be written in the same folder where data was read, named "out\_[time\_step\_counter].vtu". Open these files with Paraview to inspect simulation results.

## 6.5 The Amiata structured 3D grid case

In this example will be show how to handle material assignation of a pre-existing numerical "empty model" using raster surface.

In the folder "\ExampleData\ 05\_Amiata3D\Structured\_3D" you will find the following files: 01dem.dat 01dem.dat.ply 02fractured.dat 02fractured.dat.ply 03caprock\_shal.dat 03caprock\_shal.dat.ply 04shallow\_res.dat 04shallow\_res.dat.ply 05caprock\_deep.dat 05caprock\_deep.dat.ply 06bottom-5000.dat 06bottom-5000.dat.ply voro.par MESH

tough2viewer.dat

Each file represents the top surface of a different geological layer. In this example we just focus our attention on the rocktype assignation, without considering petrophysical properties of the geological layer, to be treated separately in the ROCKTYPE section of the TOUGH2 input file.

The coordinates of the surface and of the model are referred to geographical coordinates.

The limit of the domain of the numerical model are (m):

x\_max=1726500.00 x\_min=1701500.00 y\_max=4759500.00 y\_min=4732500.00 z\_max=2000.00 z\_min=-6000.00

The empty model builded using VORO2MESH, is composed by:

| x_max        | x_min   | y_max   | y_min   | z_max | z_min |
|--------------|---------|---------|---------|-------|-------|
| 1726500      | 1701500 | 4759500 | 4732500 | 2000  | -6000 |
| Lx=          | 25000   | Ly=     | 27000   | Lz=   | 8000  |
| nx           | 25      | ny      | 27      | nz    | 40    |
| Tot. Blocks  | 27000   |         |         |       |       |
| Block dimens | ions    |         |         |       |       |
| dx=          | 1000    | dy=     | 1000    | dz=   | 200   |

Table 1 - Domain bound and grid information

We are using a finer discretization in the vertical direction.

The dimensions of the blocks are: 1000x1000x200 m<sup>3</sup>.

Open TOUGH2Viewer and from the menu "file" select "Open unstructured V++ grid..." and then select the tough2viewer.dat file and the MESH file from the example folder. Close the dialog by selecting the close button.

From the menu "file" select "Import Surface File..." and then select, in the following order, the files:

- 01dem.dat
- 02fractured.dat
- 03caprock\_shal.dat
- 04shallow\_res.dat
- 05caprock\_deep.dat
- 06bottom-5000.dat

After surfaces importation procedure finishes, the **Import Shapefile** dialog window will be as shown in Fig. 74.

| 🛓 Import shapefile   |                | _ |    | ×   |
|--|----------------|---|----|-----|
| add new Load last  |                |   |    |     |
| ShapeFileName  | Polyline Color |   |    |     |
| 01dem.dat<br>02fractured.dat<br>03caprock_shal.dat<br>04shallow_res.dat<br>05caprock_deep.dat<br>06bottom-5000.dat |                |   |    |     |
|  |                |   | Cl | ose |

Fig. 74 – ImportShapeFile window after surface file importing.

Optionally, user can modify the aspect ratio of the model and of the surface shape by selecting from the menu **Options->3D Block model** object a Z Stretch Factor=5, then click **apply** (Fig. 75).

|   |  |                              |                 |                         | _   |    |
|---|--|------------------------------|-----------------|-------------------------|-----|----|
| Options   |  |                              |                 | —                       |     | ×  |
| Visualization Filter 3D Block model Object  | 3D Flow model Misc.  | Skins Plot Form              | nat             |                         |     |    |
| Appearance<br>Light one Axis<br>Light two Choose Background<br>Light three Ambient light<br>Material<br>1 | Block Stretch<br>Reduce Block Facto<br>Z Stretch Factor<br>Zoom factor | r (0.5-1.0) 0.85<br>5<br>1.0 | Visible         | Apply<br>Apply<br>Apply |     |    |
|   |  |                              |                 |                         |     |    |
|   |  |                              |                 | Print                   |     |    |
| Shapefile Color   | Con  | ntour line visible           | Surface visible |                         |     |    |
| 01dem.dat   |  | ~                            | ✓               |                         |     |    |
| 02cractured.dat   |  | <u> </u>                     | ✓               |                         | Clo | se |
| 04shallow_res_dat   |  |                              | ✓               |                         |     |    |
| 05caprock_deep.dat  |  | ~                            | ×               |                         |     |    |
| 06bottom-5000.dat   |  |                              | V               |                         |     |    |
|   |  |                              |                 |                         | ]   |    |

Fig. 75 – Options dialog window, **3D Block model** tab.

From the View menu, select **View->3D Block model**. The starting view is the top view. Rotate the model and obtain the representation as shown in Fig. 76



Fig. 76 - The empty 3D structured model and the surfaces.

Select from the Action dropdown menu the **AdvancedBlockSelection** command. From the **AdvancedBlockSelection** dialog window (Fig. 77), select **above** and **01dem.dat** surface selection. Press **Add**.

| AdvancedBlockSelection   | on  |  | _ | × |
|--|---|--|---|---|
| Block Selection          A11 1       ✓         AAAAA       sea         Add       Rem         RockType Selector       Select Rocktype         Select Rocktype       1 ✓ | Block information<br>BlockName=<br>Xo=<br>Yo=<br>Zo=<br>Rocktype=<br>Add Remove | General<br>ResetSelection<br>InvertSelection<br>Select Visible blocks<br>Open Modfy Selectio |   |   |
| Surface Selector<br>Select blocks that are<br>Select blocks that are   | Above v the surface 01de<br>Inside v the surfaces:<br>and the surface 01de      | em.dat V Add Remove  |   |   |
| Pick Options <ul> <li>Add</li> <li>Same 2</li> <li>Same 2</li> <li>Same 2</li> <li>Same 2</li> <li>Same 2</li> </ul>   | X SameXY (along Z)<br>Y SameXZ (along Y)<br>Z SameYZ (along X)                  | Close  |   |   |

Fig. 77 – Advanced Block Selection dialog window

All the blocks that have the coordinates block node **above** the selected surface will be selected. Press the **Open Modify Selection**... button.

On the **Properties modifier** dialog window (Fig. 78) insert using the **New Rocktype** text box a new rocktype name "**ATMO1**". Then click **Apply**.

| 🛓 Properties | modifier    |        | _     |   | ×    |
|--------------|-------------|--------|-------|---|------|
|              |             |        |       |   |      |
| Rocktype     | 1           | $\sim$ | Apply |   |      |
| New Rocktype | ATMO1       |        | Apply |   |      |
| Volume       | 1.0E55      |        | Apply |   |      |
|              |             | 1      |       |   |      |
| Load Sele    | ction       |        |       |   |      |
| SaveThisSe   | lection     |        |       |   |      |
| ExportThisSe | election    | ]      |       |   |      |
| ExportTheMo  | odifiedGrid | ]      |       |   |      |
|              |             |        |       | C | lose |

Fig. 78 - properties modifier dialog window

Close the **Properties modifier** dialog window. In the **AdvancedBlockSelection** dialog window press **ResetSelection** and confirm.



The model rocktypes has then been modified as shown in Fig. 79.

Fig. 79 – The modified model after rocktype assignation

Select now the **Inside** dropdown menu block selector from the **AdvancedBlockSelection** dialog window, panel "surface selector" and select as first surface **01dem.dat** and as the second surface the **02fractured.dat** record. Note that the selected blocks are hidden from the **ATMO1** type blocks. Open the **Options** dialog window and hide the ATMO1 blocks type and, optionally, the 01dem.dat surface. Open the **Properties modifier** dialog window and assign the material **VULC2**.

By repeating these steps, assign the materials types to each strata, up to have a material type assignation like:

3D Block model



Fig. 80 – The final 3D structured model with the desired rocktype assignation.

| 🛓 Options   |   | - 🗆 X                   |
|---|---|-------------------------|
| Visualization Filter 3D Block model Obje  | ct 3D Flow model Misc. Skins Plot Format                                      |                         |
| Appearance         Light one       Axis         Light two       Choose Background         Light three       Ambient light | Block StretchReduce Block Factor (0.5-1.0)0.85Z Stretch Factor5Zoom factor1.0 | Apply<br>Apply<br>Apply |
| Material  | Color Visible   |                         |
|   |   | <u>~</u>                |
| CAPR1   |   | ✓                       |
| CAPR2   |   |                         |
| DEEP1   |   | <u> </u>                |
| SHAL1   |   |                         |
| VOLCI   |   |                         |
|   |   | Print                   |
| Shapefile Color   | Contour line visible St   | urface visible          |
| 01dem.dat   | $\checkmark$  |                         |
| 02fractured.dat   |   |                         |
| 03caprock_shal.dat  |   |                         |
| 04shallow_res.dat   |   |                         |
| 06bottom-5000 dat   |   |                         |
|   |   | <u> </u>                |
|   |   | Close                   |

Fig. 81 – The Option dialog window. Note the new rocktypes created during the model modifications.

User may also set the boundary condition for ATMO1 blocks type. This operation can be perfomed by selecting the ATMO1 block type using the AdvancedBlockSelection dialog window and then using the properties modifier by pressing the **Volume apply** button. This action will modify the volume of the selected block to an infinite volume (or to a volume set by the user).

Open the **Properties modifier** dialog window and press **ExportTheModifiedGrid** button. In the **Save File** dialog window choose a name for the new grid, e.g. **model01**, and click the **Save** button.

In the selected folder a new MESH and tough2viewer.dat file, named model01.dat and model01\_tough2viewer.dat respectively has been created.

User can open the new generated model again by TOUGH2Viewer in another session for grid inspection before running a TOUGH2 simulation.

Note that:

The strata **SHAL1** have some pinch-out because the distance between the 2 surfaces was near to zero and there are not blocks with the node included in these two surfaces.

## 6.6 The structured grid case

In this example will be show how to handle material assignation of a pre-existing numerical "empty model" using a set of raster surfaces.

In the folder "\\ExampleData\ 06\_Structured2D" you will find the following sub-folders:

- model;
- surfaces;
- voro2mesh;

The voro2mesh folder contains all the input data needed for the generation of the empty model, using VORO2MESH. For details about VORO2MESH, please see Bonduà et al. (2017).

In the model folder, you will find the MESH file and the tough2viewer.dat file (geometrical data) as generated by VORO2MESH.

The surfaces folder contains the surfaces files that will be used for rocktype assignation, in raster and in ply file format:

- 00top.dat;
- 00top.ply;
- 01top.dat;
- 01top.ply;
- 02top.dat;
- 02top.ply;
- 03top.dat;
- 03top.ply;

A graphical representation of these surfaces is given in Fig. 82.



Fig. 82 - The four surfaces used to define the several geological horizons. Image obtained with Paraview.

Each file represents the top surface of a different geological layer. In this presentation we just focus the attention on the rocktype assignation, without considering petrophysical properties of the geological layer, to be treated separately in the ROCKTYPE section of the TOUGH2 input file. The limits of the domain of the numerical model are (m):

x max=+5000.0 x\_min=0.0 y\_max=+1000.0  $y_{min}=0.0$ z\_max=500.0 z min=-3000.0

The dimension of the blocks are: 100x1000x100 m<sup>3</sup>.

Open TOUGH2Viewer and from the File menu select Open unstructured V++ grid...

Select the tough2viewer.dat file and the MESH file from the path: \\ExampleData\06\_Structured2D\model.

Press the **CreateEmptyModel** button and then close the dialog by selecting the **Close** button. From the File menu select Import Surface File...

Select the files in the following order:

- 00top.dat; ٠
- 01top.dat; •
- 02top.dat; •
- 03top.dat; •

| 🛓 Import shapefile                               |                | _ |   | ×     |
|--|----------------|---|---|-------|
| add new Load last                                |                |   |   |       |
| ShapeFileName                                    | PolyLine Color |   |   |       |
| 00top.dat<br>01top.dat<br>02top.dat<br>03top.dat |                |   |   |       |
|  |                |   | ( | Close |

Fig. 83 – The ImportShapefile dialog window after data loading.

From the TOUGH2Viewer View menu, select View->3D Block model. From the dropdown BlockAppearance, select the Rocktype item. The initial view is the top view. Rotate the model and obtain the representation as shown in Fig. 84.



Fig. 84 – The model and the surfaces visualized in the Model3D window.

From the **Action** menu, select the **AdvanceBlockSelection** command. The AdvanceBlockSelection dialog window of Fig. 85 will be shown.

| AdvancedBlockSelection   |  | _ | × |
|--|--|---|---|
| Block Selection<br>A11 1<br>Block information<br>BlockName=<br>Xo=<br>AAAAAA sea Yo=<br>Zo=<br>Add Rem Rocktype=   | General ResetSelection InvertSelection Select Visible blocks Open Modify Selection |   |   |
| RockType Selector         Select Rocktype       1          Add       Remove         Surface Selector         Select blocks that are       Above          Select blocks that are       Inside         Select blocks that are       Inside | o.dat V Add Remove   |   |   |
| 00top.dat v and the surface 00top  | o.dat ~ Add Remove   |   |   |
| Pick Options <ul> <li>Add</li> <li>Same X</li> <li>SameXY (along Z)</li> <li>Remove</li> <li>Same Y</li> <li>SameXZ (along Y)</li> <li>Same Z</li> <li>SameYZ (along X)</li> </ul>   |  |   |   |
|  | Close  |   |   |

Fig. 85 – The AdvanceBlockSelection dialog window.

From the Surface Selector panel, press the **add** button that belong to "Select blocks that are above the surface 00top.dat" line.

With this command all blocks that are above the surface 00top.dat will be selected. Press now the **Open Modify selection...** button. In the dialog window, enter a new rock type called ATMO1. Then press **Apply** (see Fig. 86).

| Properties   | modifier    |        | _     |   | ×     |
|--------------|-------------|--------|-------|---|-------|
|              |             |        |       |   |       |
| Rocktype     | 1           | $\sim$ | Apply |   |       |
| New Rocktype | ATM01       |        | Apply |   |       |
| Volume       | 1.0E55      |        | Apply |   |       |
| Load Sele    | ction       |        |       |   |       |
| SaveThisSe   | lection     |        |       |   |       |
| ExportThisSe | election    |        |       |   |       |
| ExportTheMo  | odifiedGrid |        |       |   |       |
|              |             |        |       | ( | Close |

Fig. 86 – properties modifier dialog window.

Close the window and in the **AdvancedBlockSelection** press the **ResetSelection** button. The model will now appear as shown in Fig. 87.

In the Surface Selector panel of the AdvancedBlockSelection dialog window, press the add button relatively to the command "Select blocks that are inside the surface 00top.dat and the surface 01top,dat". By the **Open Modify Selection** command, assign to the selected blocks a new rocktype **CAPR2**.

The model is now modified as shown in Fig. 89.

By repeating the above procedure by changing the surfaces, a final model can be obtained. A view of the final model is shown in Fig. 90.



Fig. 87 – The modified grid.



Fig. 88 – The block selection between two surfaces.



Fig. 89 – The modified grid.



Fig. 90 – The final grid.

User can change the rocktype color by the **Tool->Option** dialog window. In the Fig. 91 is shown the same model of Fig. 90 with the color of rocktypes changed and the surfaces colored by rocktype. Also a setVOI command is applied to the visualization.



Fig. 91 – The final model with modified colors and VOI applied.

After rocktype assignation and/or blocks volume editing, the modified model must be saved by using the **ExportTheModfiedGrid** command of the **PropertiesModifer** dialog window. In Fig. 92 is shown the save dialog window after pressing the **ExportTheModifiedGrid** button. Note that in the same folder will be saved also a copy of the tough2viewer.dat, because in case of a generation of a sub grid, a different geometry file is needed.

| 🙆 Properties modifier 🦳 🗆 🗙 | 😹 Salva                   | ×       |
|-----------------------------|---------------------------|---------|
|                             | Salva in: 📜 model 🗸 🖉 📖 🗸 |         |
| Rocktype 1 V Apply          | MESH                      |         |
| New Rocktype ABCDE Apply    | Oggetti rec               |         |
| Volume 1.0E55 Apply         |                           |         |
| Load Selection              | Desktop                   |         |
| SaveThisSelection HOT##     | Documenti<br>Questo PC    |         |
| ExportThisSelection         |                           |         |
| ExportTheModifiedGrid       | Nome file: modified_grid  | Salva   |
| Close                       | Tipo file: Tutti i file V | Annulla |

Fig. 92 – The modified grid is saved as "modified\_grid".

#### **INCON** generation

Before creating a new INCON file, a previous INCON or SAVE file must be loaded.

Load the INCON.dat file by the **Open Unstructured V++ grid...** dialog window.

In the **AdvancedBlockSelection** dialog window, press the **Generate INCON** button or, alternatively, from the TOUGH2Viewer main menu **select Tools->Create INCON**. The **INCON Generator** dialog window will be shown. From the variable selector select INCON\_0 and then press the **add** button. Repeat the previous step up to the INCON\_3 variable. Select from the **INCON VARIABLES** selector the INCON\_0 variable and update the plot by pressing the **UpdatePlot** button. The INCON Generator dialog will now have the aspect of Fig. 93.



Fig. 93 - The INCON generator dialog window

Select the **basic** tab. This tab allows one to build/edit the INCON variable by means of a linear function. Press the P button (Pressure) to load default parameter for hydrostatic condition. Press the **zero to top** button to modify the equation in a manner that the top blocks have the pressure of the **Zero** text field (by default, atmospheric pressure for the top blocks). Press the **Preview** button to visualize the new INCON before applying changes. The INCON Generator dialog window appear now as shown in Fig. 94.



Fig. 94 - The INCON generator dialog window with a preview of the linear function.

After pressing the **Apply** and **Preview** buttons again, the variable are modified as shown Fig. 95. Repeat the previous steps for INCON\_1 (temperature), INCON\_2 (XCO2) and INCON\_3 (XNACL). It worth to mention that the tool allows one to apply the changes to all the blocks, to the blocks of a certain rocktype or just to the selected blocks.

Once that the INCON has been modified, user can visualize the new values in to the Model3D visualization window by choosing the variable to be visualized by selecting the variable to plot. To save the edited INCON file, a **write out** tab is designed to obtain the formatted INCON file as required by TOUGH. Press the **write out** tab and the **preview** button. The dialog window now displays a preview of the INCON file (see Fig. 96). Note that the numbering format can be changed by the user if the particular EOS used for the numerical simulation require a special format.



Fig. 95 – The INCON generator dialog window after changes are applied.

| are INCON Write OLIT   |  |
|--|--|
| internetion of the state of the |  |
|  |  |
|  |  |
| ormat Strings:   |  |
| .OCKNAME (5 CHARS)+ \n   |  |
| ICON VARIABLES %19e  |  |
| ND OF LINE \n  |  |
|  |  |
| review: Update Preview   |  |
| NCON1*2*3*5*6*8  |  |
| 11 1<br>3.454330e+07 1.000000e-06 0.000000e+00 1.235000e+02  |  |
| 21 1<br>3.353030e+07 1.000000e-06 0.000000e+00 1.205000e+02  |  |
| 31 1<br>3.251730e+07 1.000000e-06 0.000000e+00 1.175000e+02  |  |
| 41 1   |  |
| 5.1504504+07 1.000000-00 0.0000000+00 1.145000+02  |  |
| 3.049130e+07 1.000000e-06 0.000000e+00 1.115000e+02<br>.61 1   |  |
| 2.947830e+07 1.000000e-06 0.000000e+00 1.085000e+02<br>.71 1   |  |
| 2.846530e+07 1.000000e-06 0.000000e+00 1.055000e+02<br>.81 1   |  |
| 2.745230e+07 1.000000e-06 0.000000e+00 1.025000e+02  |  |
| 2.643930e+07 1.000000e-06 0.000000e+00 9.950000e+01  |  |
| AL 1<br>2.542630e+07 1.000000e-06 0.000000e+00 9.650000e+01  |  |
| B1 1<br>2.441330e+07 1.000000e-06 0.000000e+00 9.350000e+01  |  |
| C1 1   |  |
| 2.340030e+07 1.000000e-06 0.000000e+00 9.050000e+01 ♥  |  |

Fig. 96 – The INCON generator preview dialog window.

As last step, press the **Choose File to save as...** button to generate the new INCON file. The created file will be [inserted name file].INCON.

The generated files (the MESH and the INCON file) are now ready to be used in a TOUGH simulation.

It worth mentioning that the number of primary variables written in to the INCON file have to match with the number of variables required by the specific EOS - TOUGH simulator and option, and no-check or validation will be performed on it by TOUGH2Viewer.

## 7 References

Battistelli, A, Calore, C., Pruess K., 1997. The simulator TOUGH2/EWASG for modelling geothermal reservoirs with brines and a non-condensable gas. Geothermics 26(4):437–464.

Berry, P., Bonduá, S., Bortolotti, V., Cormio, C., Vasini, E.M., 2014. A GIS-based open source preprocessor for georesources numerical modeling, Environmental Modelling & Software, 62, 52-64, ISSN 1364-8152.

Bonduá, S., Berry, P., Bortolotti, V., Cormio, C. (2012). TOUGH2Viewer: A post-processing tool for interactive 3D visualization of locally refined unstructured grids for TOUGH2. Computers & Geosciences, 46, p. 107-118.

Bonduà, S.; Battistelli, A.; Berry, P.; Bortolotti, V.; Consonni, A.; Cormio, C.; Geloni, C.; Vasini, E. M., (2017). 3D Voronoi grid dedicated software for modeling gas migration in deep layered sedimentary formations with TOUGH2-TMGAS, COMPUTERS & GEOSCIENCES, *in press*.

Pruess, K., Oldenburg, C., Moridis, G., 1999. TOUGH2 User's Guide, Version 2.0, Report LBNL-43134. Lawrence Berkeley National Laboratory, Berkeley, California, (Report LBNL-43134).

# 8 List of figures

| Fig.   | 1 – Java Folder  | 4    |
|--------|--|------|
| Fig. 2 | 2 – j3dcore-ogl.dll location   | 4    |
| Fig. 3 | 3 – j3dcore.jar, j3dutil.jar and vecmath.jar folder  | 5    |
| Fig. 4 | 4 – (a) TOUGH2Viewer main dialog (b) File menu items                                       | 9    |
| Fig. 5 | 5 – TOUGH2Viewer View menu   | 10   |
| Fig. ( | 6 – TOUGH2Viewer Analysis menu   | 12   |
| Fig. 7 | 7 – TOUGH2Viewer Tools menu  | 13   |
| Fig. 8 | 8 - The TOUGH2Viewer empty main window   | 14   |
| Fig. 9 | 9 - The "Open structured grid" dialog window.  | 15   |
| Fig.   | 10 - Main window with geometric information of the loaded grid.                            | 15   |
| Fig.   | 11 - 3D Default representation of the Model, Top View                                      | 16   |
| Fig.   | 12 - 3D representation of the model, FrontView.  | 16   |
| Fig.   | 13 - Pressure contour map  | 17   |
| Fig.   | 14 - Temperature contour map   | 17   |
| Fig.   | 15 - Vector map of the heat flow.  | 18   |
| Fig.   | 16 - Vector map of the variable VEL(LIO.).   | 18   |
| Fig.   | 17 - Min and Max value for simulation data. The default plot is first variable vs time     | 19   |
| Fig.   | 18 - Open Structured grid dialog.  | 20   |
| Fig.   | 19 - Open unstructured V++ grid dialog window  | 21   |
| Fig. 2 | 20 - 3D Block model window, top view   | 22   |
| Fig. 2 | 21 - 3D Block model box showing the Temperature variable at the time step 2                | 22   |
| Fig. 2 | 22 - 3D modelFrame horizontally sectioned.   | 23   |
| Fig. 2 | 23 – Graph of the pressure versus the x coordinate   | 23   |
| Fig. 2 | 24 – Graph of the pressure versus the z coordinate.  | 24   |
| Fig. 2 | 25 – Graph of the pressure versus the z coordinate, with background coloring               | 24   |
| Fig. 2 | 26 - ExpandZ command result  | 25   |
| Fig. 2 | 27 - QuickInfo command result, information are printed in a panel at the bottom of the win | dow. |
|        |  | 26   |
| Fig. 2 | 28 - SetVOI function applied to the model  | 26   |
| Fig. 2 | 29 - 3D Block model in material color scale.   | 27   |
| Fig. 3 | 30 - Vector representation of the heat flow.   | 27   |
| Fig. 3 | 31 - Vertical heat flow profile  | 28   |
| Fig. 3 | 32 - 3D IsoSurface dialog.   | 28   |
| Fig. 3 | 33 - IsoSurface Dialog for pressure and time step 0  | 29   |
| Fig. 3 | 34 - Dialog window for the pressure IsoSurface.  | 30   |
| Fig. 3 | 35 - 2D Contour Plot for the Pressure (Pa)   | 31   |
| Fig. 3 | 36 - TOUGH2Viewer empty main window  | 32   |
| Fig. 3 | 37 - Open unstructured grid dialog window  | 32   |
| Fig.   | 38 - TOUGH2Viewer main window that summarizes some geometric data of the lo                | aded |
| nume   | erical model   | 33   |
| Fig. 3 | 39 - Import shapefile dialog window  | 33   |
| Fig. 4 | 40 - Dialog window to load shape files.  | 33   |
| Fig. 4 | 41 - Dialog window to select the file to be loaded.  | 34   |
| Fig. 4 | 42 - 2D Preview of the base_ss.shp file  | 34   |
| Fig. 4 | 43a, b - LoadShpFile Dialog window   | 35   |
| Fig. 4 | 44 - Import shapefile window. The table resume imported shape files                        | 35   |
| Fig. 4 | 45 – "Choose a color" dialog window window.  | 36   |
| Fig. 4 | 46 - Top view of the 3D Block model  | 36   |
| Fig. 4 | 47 - SetVOI dialog window  | 37   |
| Fig. 48 -                               | (a) 3D model partially showed and block selected (white block); (b) information related | l to       |
|---|---|------------|
| the selec                               | ted block   | .37        |
| Fig. 49 -                               | Find Block dialog window.   | .38        |
| Fig. 50 -                               | Snapshot Preview window dialog window.  | .38        |
| Fig. 51 -                               | 3D Block Model front view. Material color scale.  | . 39       |
| Fig. 52 -                               | Options dialog window.  | .39        |
| Fig. 53 -                               | Options dialog with modified parameters.  | .40        |
| Fig. 54 -                               | 3D Block model  | .40        |
| Fig. 55 -                               | Profiles dialog which shows the pressure values along z axis.                           | .41        |
| Fig. 56 -                               | Bottom filtered view of the 3D model with modified color scale                          | .41        |
| Fig. 57 -                               | 3D Flow vector default viewing.   | .42        |
| Fig. 58 -                               | 3D Flow model at the time step 1 for the variable VEL(GAS)                              | .42        |
| Fig. 59 -                               | 3D IsoSurface dialog window.  | .43        |
| Fig. 60 -                               | Isosurface for T=270°C, time step "6"   | .43        |
| Fig. 61 –                               | Temperature isolines contour map  | .44        |
| Fig. 62 -                               | TOUGH2Viewer empty main window  | .45        |
| Fig. 63 –                               | Input unstructured grid window  | .45        |
| Fig. 64 –                               | The main window   | .46        |
| Fig. 65 -                               | Top view of the 3D Block model  | 46         |
| Fig. 66 -                               | View of the SG thermodynamic variables (3D Block model)                                 | 47         |
| Fig. 67 –                               | - MultipleSelection command   | 47         |
| Fig. $68 =$                             | Properties modifier GUI   | 48         |
| Fig. $60 =$                             | The generated ASCII file  | 48         |
| Fig. $70$                               | The modified GENER file   | 18         |
| Fig. $70 -$                             | INCON generator dialog window   | 0<br>/0    |
| Fig. $71 - 72$                          | INCON generator dialog window preview   | 50         |
| Fig. $72 =$                             | INCON generator dialog window preview   | 51         |
| Fig. $73 =$                             | Import Shape File window after surface file importing                                   | 52         |
| Fig. 74 -                               | Options dialog window   | 51         |
| Fig. 75 - Fig. 76                       | The exercise 2D exercises down doll and the exercise and                                | . 34       |
| Fig. 70 –                               | - The empty 3D structured model and the surfaces  | . 33       |
| Fig. // –                               | - Advanced Block Selection dialog window  | . 36       |
| Fig. 78 –                               | properties modifier dialog window   | . 36       |
| Fig. /9 –                               | The modified model after rocktype assignation   | .57        |
| Fig. 80 –                               | The final 3D structured model with the desired rocktype assignation.                    | .58        |
| Fig. 81 –                               | The Option dialog window. Note the new rocktypes created during the model modification  | ns.        |
| Eig 82                                  | The four surfaces used to define the several geological herizons. Image obtained w      | JO<br>vith |
| Fig. 62 -                               | - The four surfaces used to define the several geological horizons. Image obtained w    | 60         |
| Fig 82                                  | The Import Shapefile dialog window after data leading                                   | 61         |
| Fig. $03 -$                             | The model and the surfaces visualized in the Model2D window                             | 62         |
| $\frac{\Gamma \log 04}{\Gamma \log 05}$ | The Advance Diock Scientian dialog window.  | 62         |
| $Fig. \delta J = E_{1}^{2} \delta J$    | - The AdvanceblockSelection dialog window   | .02        |
| Fig. 86 –                               | - properties modifier dialog window   | .03        |
| Fig. $8/-$                              | The modified model.   | .63        |
| F1g. 88 –                               | The block selection between two surfaces  | .64        |
| F1g. 89 –                               |   | .64        |
| Fig. 90 –                               | The final model.  | .65        |
| Fig. 91 –                               | The final model with modified colors and VOI applied                                    | .65        |
| Fig. 92 –                               | The modified grid is saved as "modified_grid"   | .66        |
| Fig. 93 –                               | The INCON generator dialog window   | .67        |
| Fig. 94 –                               | The INCON generator dialog window with a preview of the linear function                 | .68        |
| Fig. 95 –                               | The INCON generator dialog window after changes applied.                                | .69        |

| Fig. | 96 – The INCON | I generator preview | dialog window |  |
|------|----------------|---------------------|---------------|--|
|------|----------------|---------------------|---------------|--|